



EclecticIQ Platform integrations

Integrate with external tools in your cyber security ecosystem

Last generated: October 20, 2017



©2017 EclecticIQ

All rights reserved. No part of this document may be reproduced in any form or by any electronic or mechanical means, including information storage and retrieval systems, without written permission from the author, except in the case of a reviewer, who may quote brief passages embodied in critical articles or in a review.

Trademarked names appear throughout this book. Rather than use a trademark symbol with every occurrence of a trademarked name, names are used in an editorial fashion, with no intention of infringement of the respective owner's trademark.

The information in this book is distributed on an "as is" basis, without warranty. Although every precaution has been taken in the preparation of this work, neither the author nor the publisher shall have any liability to any person or entity with respect to any loss or damage caused or alleged to be caused directly or indirectly by the information contained in this book.

©2017 by EclecticIQ BV. All rights reserved.
Last generated on Oct 20, 2017

Table of contents

Table of contents	2
EclecticIQ Platform integrations	5
Feedback	5
Cisco OpenDNS integration	6
Configure the enricher	6
Configure enricher tasks	7
Configure enricher rules	7
Add enricher rules	7
Save options	8
Edit enricher rules	8
Delete enricher rules	9
Run the enricher	10
Automatically	10
Manually	10
Review enrichment observables	14
Review enrichment observables on the graph	15
Search for enrichment observables	17
Cisco Threat Grid integration	21
Configure Cisco Threat Grid as an incoming feed	21
Configure the general options	21
Configure the transport type	22
Cisco Threat Grid API	22
Set a schedule	22
Set a TLP override	23
Set half-life values	23
Save options	24
Configure Cisco Threat Grid as an enricher	24
Configure enricher tasks	25
Configure enricher rules	26
Add enricher rules	26
Save options	27
Edit enricher rules	27
Delete enricher rules	28
Run the enricher	28
Automatically	28
Manually	28
Review enrichment observables	32
Review enrichment observables on the graph	33
Search for enrichment observables	35
Flashpoint integration	39
Configure the enrichers	39
Configure enricher tasks	39
Configure enricher rules	40
Add enricher rules	40
Save options	41
Edit enricher rules	41
Delete enricher rules	42
Run the enricher	43
Automatically	43
Manually	43
Review enrichment observables	47
Review enrichment observables on the graph	48
Search for enrichment observables	50
PassiveTotal integration	54
Configure the enrichers	54
Configure enricher tasks	54
Configure enricher rules	55
Add enricher rules	55

Save options	56
Edit enricher rules	56
Delete enricher rules	57
Run the enricher	58
Automatically	58
Manually	58
Review enrichment observables	62
Review enrichment observables on the graph	63
Search for enrichment observables	65
VirusTotal integration	69
Configure the enricher	69
Configure enricher tasks	70
Configure enricher rules	71
Add enricher rules	71
Save options	72
Edit enricher rules	72
Delete enricher rules	73
Run the enricher	73
Automatically	74
Manually	74
Review enrichment observables	77
Review enrichment observables on the graph	78
Search for enrichment observables	80
Splunk integration	84
Release notes	84
Contact	84
About EclecticIQ Platform App for Splunk	84
Quick start guide	85
Compatibility	85
Install	85
Configure	86
Uninstall	87
Install and configure Python	87
EclecticIQ Platform integration with Splunk	88
Before you start	88
Requirements	88
Process outline	88
Configure EclecticIQ CSV outgoing feeds	89
Configure the general options	89
Set a schedule	90
Set a TLP override	91
Set reliability and relevancy	91
Set observable filters	92
Save options	92
Configure the transport type	92
HTTP download	92
Mount point upload	93
Configure the content type	93
Create an automation user and group	94
Create an automation group	94
Save options	95
Create an automation role	95
About permissions	95
Create an automation user	96
Get the automation group meta.source ID	97
Step 1 of 2: get the group ID	97
Step 2 of 2: get the group source ID	97
Get the automation group meta.source ID example	97
Get the group ID	97
cURL API request — fetches the group meta.source	98

API response — returns the group meta.source	98
Authentication	99
Auth request	100
Auth response	100
Get the feed ID	101
Get the feed ID through the GUI	101
Get the feed ID through the API	101
API request outgoing feeds	102
API response outgoing feeds	102
Get a specific outgoing feed	103
API request specific outgoing feed	103
API response specific outgoing feed	103
Install and configure EclecticiQ Platform App for Splunk	104
Download the app	104
Install the app	104
Configure the app	104
Configure data model acceleration	107
Default job schedule	109
Customize the job schedule	109

EclecticIQ Platform integrations

EclecticIQ Platform integrations with third-party products and systems to leverage external intel sources and improve collaboration.

Browse the table for the topics you want to look up.

You can also use the drop-down menu on the left-hand navigation sidebar to access the articles or to go to a different section.

Title	Excerpt
Cisco OpenDNS integration	Integrate EclecticIQ Platform with Cisco OpenDNS through OpenResolve by OpenDNS to retrieve reverse DNS lookup information.
Cisco Threat Grid integration	Integrate EclecticIQ Platform with Cisco Threat Grid through the Threat Grid API. You can implement the integration as an incoming feed to ingest entities, as well as an enricher to produce enrichm...
Build custom enrichers	Implement custom extensions to integrate EclecticIQ Platform with external intel providers through incoming feeds and enrichers, as well as to publish platform intel downstream in your prevention/d...
Flashpoint integration	Integrate EclecticIQ Platform with Flashpoint AggregINT, Flashpoint Blueprint, and Flashpoint Thresher through the Flashpoint API.
Intel 471 integration	Integrate EclecticIQ Platform with Intel 471 through the Intel 471 API. You can implement the integration as an incoming feed to ingest entities, as well as an enricher to produce enrichment observ...
PassiveTotal integration	Integrate EclecticIQ Platform with RiskIQ PassiveTotal to retrieve active/passive DNS, IP, domain, and malware information.
Splunk integration	EclecticIQ Platform App for Splunk Enterprise enables Splunk users to ingest large quantities of threat intelligence by integrating EclecticIQ Platform feeds with Splunk Enterprise.
VirusTotal integration	Integrate EclecticIQ Platform with VirusTotal to retrieve malware information about DNSs, IPs, domains, and files.

Feedback

No one reads manuals, ever. We know.

Yet, we strive to give you clear, concise, and complete documentation that helps you get stuff done neatly.

We are committed to crafting good documentation, because life is too short for bad doc.

We appreciate your comments, and we'd love to hear from you: if you have questions or suggestions, drop us a line and share your thoughts with us!

 The Product Team

Cisco OpenDNS integration

Integrate EclecticIQ Platform with Cisco OpenDNS through OpenResolve by OpenDNS to retrieve reverse DNS lookup information.

Cisco OpenDNS OpenResolve	integration
Integration	OpenDNS OpenResolve
Type	enricher
API endpoint	<code>http://api.openresolve.com/{}/{}</code>
Input	domain, host, ipv4, ipv6
Output	Enriches supported observable types with reverse-DNS lookup information.
Description	OpenResolve by OpenDNS offers a REST API to use DNS resolvers and to retrieve reverse-DNS lookup information.

EclecticIQ Platform integrates with Cisco OpenDNS solutions to use them as intel sources. The platform integrates with the Cisco OpenDNS OpenResolve API through an enricher.

To enable the Cisco OpenDNS integration you configure the Cisco OpenDNS/OpenResolve enricher as needed, and then activate it or run it manually to poll the intel source.

Configure the enricher

Enrichment rules and enrichment tasks drive the enrichment process to:

- Poll selected and trustworthy intelligence data sources;
- Retrieve relevant, accurate, and reliable data to augment platform entities with additional bits of information that provide additional context.

Rules

Enrichment rules define what to do with the retrieved enrichment data.

Rules act like filters, and they set the logical constraints defining:

- The platform data sources to augment with enrichment information.
Data sources you can enrich are incoming feeds, other enrichers, and groups.
- Within the selected platform data sources, the entity type(s) to augment with enrichment information.
- The enrichers to use to fetch enrichment data.

Tasks

Enrichment tasks define process execution by setting the following options:

- The data fetching mechanism — for example, an API endpoint exposing the enrichment data service.
- Specific data sources — for example, datasets targeting threat actors like hackers and terrorist groups.

- Data rate limit and monthly execution cap values to control the amount of polled data.
- A source reliability flag for the incoming enrichment data to simplify assessing the quality of the retrieved data.

Observables

Observables augment the entities they are related to by providing additional context that can help discover indirect relationships or spawn new relationships between entities.

Observables are atomic and factual: an observable represents one discrete piece of information that describes a fact. For example, an IP address, a hash value, the name of a location or an actor.

Configure enricher tasks

To configure or to edit an enricher task, do the following:

- On the top navigation bar click **Data configuration > Enrichers**.
- On the enricher overview page click the tile corresponding to the enricher you want to configure or modify.
- On the enricher detail page click the **Edit** button.

✔ Input fields marked with an asterisk are required.

- **Observable types:** select one or more observable types you want to enrich with data retrieved through the Cisco OpenDNS enricher.
Supported observable types:
 - *domain*
 - *host*
 - *ipv4*
 - *ipv6*

The Cisco OpenDNS enricher has no specific parameters to configure.

- To modify the general options for the enricher, click **Edit**.
- Click **Save** to store your changes, or **Cancel** to discard them.

Configure enricher rules

Add enricher rules

To add a new enricher rule, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment**.

- The **Rules > Enrichment** page shows an overview of the configured enricher rules. You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.
- Click the **+** icon.

✓ Input fields marked with an asterisk are required.

On the **Create enrichment rule** page, fill out the fields to create the new enricher rule:

- **Name:** define a name to identify the rule. It should be descriptive and easy to remember.
- **Description:** additional textual details. If you want, you can add a short description to provide more information and context.
- Click **+ Add** or **+ More** to add a filtering option.
- **Source:** from the drop-down menu select the incoming feed, enricher, or group whose entities and observables you want to augment with additional information.
- **Entity types:** from the drop-down menu select the entity types you want to enrich with additional information.
- **TLP:** from the drop-down menu select the TLP color code you want to use to filter enrichment data. **TLP** (<https://www.us-cert.gov/tlp>) provides an intuitive reference to assess how sensitive information is, focusing in particular on how serious it is, and whom it should or should not be shared with.
- Click **+ Add** or **+ More** to add a new filtering option. For example, to include another incoming feed or a different entity type. A filter can take only one source and one entity type at a time, but you can set up rules with as many filters as you need.
- **Enrichers:** from the drop-down menu select one or more enrichers to apply the rule to. When a rule is applied to one or more enrichers, it filters the enrichment data polled from the enricher source, based on the specified rule filters and criteria.
- Select the **Enabled** checkbox to enable the rule immediately after creating it.
- Click **Save** to store your changes, or **Cancel** to discard them.

Save options

Besides committing current data by clicking **Save**, you can also click the downward-pointing arrow on the **Save** button to display a context menu with additional save options:

- **Save and new:** saves the current data for the active item, and it allows you to start creating a new item of the same type right away. For example, a dataset, a feed, a rule, a workspace, or a task.
- **Save and duplicate:** saves the current data for the active item, and it creates a pre-populated copy of the same item, which you can use as a template to speed up manual creation work.

Edit enricher rules

To edit enricher rules, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment**.

- The **Rules > Enrichment** page shows an overview of the configured enricher rules. You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.

To edit the details of a specific rule, do the following:

- Click an area on the row corresponding to the rule you want to examine. An overlay slides in from the side of the screen to display the rule detail pane.
- On the rule detail pane click **Actions > Edit**.

Alternatively:

- Click the  icon on the row corresponding to the enricher you want to configure or modify.
- From the drop-down menu select **Edit**.

✓ Input fields marked with an asterisk are required.

- **Name:** define a name to identify the rule. It should be descriptive and easy to remember.
- **Description:** additional textual details. If you want, you can add a short description to provide more information and context.
- **Source:** from the drop-down menu select the incoming feed, enricher, or group whose entities and observables you want to augment with additional information.
- **Entity types:** from the drop-down menu select the entity types you want to enrich with additional information.
- **TLP:** from the drop-down menu select the TLP color code you want to use to filter enrichment data. **TLP** (<https://www.us-cert.gov/tlp>) provides an intuitive reference to assess how sensitive information is, focusing in particular on how serious it is, and whom it should or should not be shared with.
- Click **+ Add** or **+ More** to add a new filtering option. For example, to include another incoming feed or a different entity type.
- **Enrichers:** from the drop-down menu select one or more enrichers to apply the rule to. They are external data providers that are polled to obtain relevant enricher raw data; for example, whois lookup, reverse DNS, or GeoIP information.
- Select the **Enabled** checkbox to enable the rule immediately after creating it.
- Click **Save** to store your changes, or **Cancel** to discard them.

Delete enricher rules

To delete an enricher rule, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment**.
- The **Rules > Enrichment** page shows an overview of the configured enricher rules. You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.

To delete a specific rule, do the following:

- Click an area on the row corresponding to the rule you want to delete. An overlay slides in from the side of the screen to display the rule detail pane.
- On the rule detail pane click **Actions > Delete**.

Alternatively:

- Click the  icon on the row corresponding to the rule you want to delete.
- From the drop-down menu select **Delete**.
- On the confirmation pop-up dialog, click **Delete** to confirm the action.
- The rule is deleted.

Run the enricher

Automatically

To automatically enrich entities, make sure enricher tasks are active, and the necessary enrichment rules are configured.

Rules give you control over the type of information you want to retrieve or exclude, and what you want to do with it. You can assign one or more enricher sources to specific observable types. You can set multiple filters to cover usage scenarios as needed. You can then examine the returned enrichment observable data, as well as route it to other devices that enforce cyber threat detection or prevention.

To run the enricher automatically, go to the enricher edit mode, and make sure the **Enabled** checkbox on the edit form is selected.

If it is deselected, check it, and then click **Save**.

Manually

To adjust enrichment behavior to manually apply it to the entities you want to enrich, do the following:

- Open an entity in edit mode.
For example, on the top navigation bar click **Browse > Published** to display an overview of the published entities available in the platform.
- On the row corresponding to the entity you want to manually enrich, click the  icon to display the context menu.
- From the drop-down menu select **Edit**.
- At the bottom of the entity editor page click the **Manually enrich** checkbox.
A new input field with a drop-down menu becomes available.
- From the drop-down menu select one or more enrichers you want to apply to the entity.

Workflow

Add to dataset

Manually enrich

Enrichers to apply

Please select one or more options

- Select all options
- CVE Search enricher
- Censys Enricher
- Circl.lu IP's related to SSL Certificate
- Circl.lu SSL Certificate Fetcher

CANCEL SAVE DRAFT PUBLISH

- Click **Save draft** to store your changes without publishing the entity, **Publish** to release the new version of the entity including your changes, or **Cancel** to discard the changes.

Alternatively, you can manually enrich an entity by selecting it; for example, from a dataset, from **Browse** or from **Discovery**.

An overlay slides in from the side of the screen to display the entity detail pane.

- On the entity detail pane, click **Observables**.
- The **Observables** tab shows an overview of the enrichment observables the entity has been augmented with.

To manually enrich the entity observables:

- Click the  refresh icon to trigger a task run that polls all the enrichers configured for the entity.

Alternatively:

- From the **Actions** pop-up menu, select **Enrich > Enrich with all**.
- The platform polls all applicable enrichers for the entity, and it enriches all the entity observables with the retrieved data.

Malicious files detected

Ingested: 06.10.2017 9:20 Incoming feed: TAXII Stand Samples TLP Not Set

OVERVIEW OBSERVABLES NEIGHBORHOOD JSON VERSIONS HISTORY

Type	Value	Relation	Sighted	Conn.	First seen	Maliciousness
hash-sha256	e3b0c44298fc1c149afb4c899...	Related +1		2	06.10.2017 9:20	
hash-sha256	d7a8fbb307d7809469ca9abc...	Related +1		1	06.10.2017 9:20	
file	readme.doc.exe	Related +1		1	06.10.2017 9:20	

Edit

Delete

Add to dataset

Add to graph

Create task

Export

Download original

Enrich

Enrich with all (5)

Censys Enricher

CrowdStrike Enricher

FireEye

Flashpoint AggregINT Enricher

Flashpoint Thresher Enricher

To poll a specific enricher:

- From the **Actions** pop-up menu, select **Enrich**, and then click the specific enricher whose task run you want to trigger.
- The platform polls the specified enricher for the entity, and it enriches all supported entity observables with the retrieved data.

Malicious files detected

Ingested: 06.10.2017 9:20 Incoming feed: TAXII Stand Samples TLP Not Set

OVERVIEW OBSERVABLES NEIGHBORHOOD JSON VERSIONS HISTORY

3 selected Deselect all Enrich Add to

Type	Value	Relation	Sighted	Conn.	Business
<input checked="" type="checkbox"/>	hash-sha256: e3b0c44298fc1c149afb4c899...	Related +1		2	
<input checked="" type="checkbox"/>	hash-sha256: d7a8fbb307d7809469ca9abcb...	Related +1		1	
<input checked="" type="checkbox"/>	file: readme.doc.exe	Related +1		1	

Enrich with all (5)
Censys Enricher
CrowdStrike Enricher
FireEye
Flashpoint AggregINT Enricher
Flashpoint Thresher Enricher

To enrich only specific observables:

- On the **Observables** tab, select the checkboxes corresponding to the observables you want to enrich.
- From the **Enrich** drop-down menu, select **Enrich with all**.
- The platform polls all applicable enrichers for the entity, and it enriches the selected entity observables with the retrieved data.

Malicious files detected

Ingested: 06.10.2017 9:20 Incoming feed: TAXII Stand Samples TLP Not Set

OVERVIEW OBSERVABLES NEIGHBORHOOD JSON VERSIONS HISTORY

2 selected Deselect all Enrich Add to

Type	Value	Relation	Sighted	Conn.	Business
<input type="checkbox"/>	hash-sha256: e3b0c44298fc1c149afb4c899...	Related +1		2	
<input type="checkbox"/>	hash-sha256: d7a8fbb307d7809469ca9abcb...	Related +1		1	
<input checked="" type="checkbox"/>	file: readme.doc.exe	Related +1		1	

Enrich with all (5)
Censys Enricher
CrowdStrike Enricher
FireEye
Flashpoint AggregINT Enricher
Flashpoint Thresher Enricher

The available enricher tasks in the drop-down menu are automatically filtered to show only the applicable enrichers for the entity.

Enrichers automatically augment all the entities that accept the enricher's content type as an observable. In other words, the observable types an entity supports define the applicable enrichers an entity can use.

Review enrichment observables

The Cisco OpenDNS enricher can take the following observable types as input:

- *domain, host, ipv4, ipv6*

The enricher uses these input data types to look for additional information to enrich existing observables with. Any entity types supporting these observable types can be enriched with OpenDNS OpenResolve.

To view enrichment information on the entity detail pane, do the following:

- Select an entity; for example, from a dataset, from **Browse** or from **Discovery**.
An overlay slides in from the side of the screen to display the entity detail pane.
- On the entity detail pane, click **Observables**.
- The **Observables** tab shows an overview of the enrichment observables the entity has been augmented with.

The screenshot displays the 'Observables' tab in the Cisco OpenDNS interface. The header shows 'Ingested: Yesterday at 23:59' and 'Incoming feed: tor'. The interface includes a navigation bar with tabs: OVERVIEW, OBSERVABLES (selected), NEIGHBORHOOD, JSON, VERSIONS, and HISTORY. Below the navigation bar is a table of observables.

Type	Value	Relation	Sighted	Conn.	First seen	Maliciousness
domain	torstatus.blutmagie.de	Description + 1	96264	02.08.2017 14:52	●●●	⋮
ipv4	194.63.141.179	OpenResolve + 4		02.08.2017 14:53	●●●	⋮
email	registry@regfish.com	Threatcrowd AP...		02.08.2017 14:53	●●●	⋮
hash-md5	e63989f8df535a14cee4a06484c...	Recorded Future		02.08.2017 14:53	●●●	⋮
hash-sha256	c27c743c64713fd2a2b36b32...	Recorded Future		02.08.2017 14:53	●●●	⋮
hash-sha512	5a9df660747757935abfcdf4...	Recorded Future		02.08.2017 14:53	●●●	⋮
email	bitwisser@googlemail.com	Recorded Future		02.08.2017 14:53	●●●	⋮
hash-sha1	4e0c92f8e8dca4d9295c7587e7...	Recorded Future		02.08.2017 14:53	●●●	⋮
hash-md5	b7532bac9c0d65b3a4a724a603...	Recorded Future		02.08.2017 14:53	●●●	⋮
hash-sha256	6ae3032f45266fd48589bfa8...	Recorded Future		02.08.2017 14:53	●●●	⋮

At the bottom of the table, it shows '1 - 10 of 123' and navigation arrows.


Review enrichment observables on the graph

To view enrichment data and their connections with other entities and observables on the graph, do the following:


- On the row corresponding to the observable you want to load on the graph, click the  icon, and then select **Add to graph**.

Type	Value	Sightings	Maliciousness	Connections	Source	Timestamp	
ipV4	217.93.38.31			1	tor	29.08.2017 9:23	
domain	pd95d261f.dip0.t-ipconnect.de			1	tor		Ignore observable Create indicator Create sighting Add to graph Set maliciousness >
ipV4	93.238.180.183			1	Gecko Indicator...		
hash-md5	961b27607e5c2f7915558e1cee520bb4			7	Gecko CS indic...		
uri	https://www.threathq.com/p42/search/default?m=7413			1	Gecko Phishme...		

- To load the parent entity whose detail pane you are viewing, instead of its observables, from the pop-up **Actions** menu at the bottom of the pane select **Add to graph**.
- Click the graph thumbnail on the lower side of the screen to expand it.
- On the graph, right-click the entity you want to inspect, and from the context menu select **Load entities > All**, **Load observables > All** or **Load entities by extract > All**.




- Right-click an extract or an entity for further inspection and from the context menu select **Load entities > All**, **Load observables > All** or **Load entities by extract > All**.




To see how entities, observables and enrichment observables are connected, and to inspect relationships between distant items, do the following:

- **CTRL + click** two nodes on the graph to select them.
- Right-click either selected node, and from the context menu select **Find path** to query the graph database about the existence of a path between the nodes, or **Show path** to highlight an existing path on the graph.
- If a path does exist, the selected nodes and all the intermediate ones are highlighted on the graph to show the path that links them.



Search for enrichment observables

You can use the search box to look for enrichment observables. You can find the search box on the top bar:



Enter search terms and search queries, and then press **ENTER** or click the search icon to run the search. Searches you run through this search box are executed platform-wide.




The search functionality uses **Elasticsearch query syntax**

(<https://www.elastic.co/guide/en/elasticsearch/reference/current/full-text-queries.html>).


To access a cheatsheet with search examples using entity types, filters, and for help with the search syntax, click **Help** to display thematic drop-down lists with common search queries:

- **Filters:** examples of quick search filters.

- **Help:** examples of regex, Boolean, wildcards, and tag search usage.
- **Entities:** examples of searchable entity types.



Besides full text search, you can use Boolean operators, wildcards, regex, and you can combine these filtering options to create more refined searches.



Use operators to combine multiple quick filters and create a more complex search query.

Example:


```
enrichment_extracts.kind:domain AND enrichment_extracts.meta.classification:high
```

Field	Description	Example
<i>enrichment_extracts.id</i>	string — The alphanumeric ID string that uniquely identifies the enrichment observable.	01h12x45-01q2-1234-od01-123456h78h90
<i>enrichment_extracts.kind</i>	string — The enrichment observable data type.	domain
<i>enrichment_extracts.meta.blacklisted</i>	Boolean — An observable is blacklisted when it is included in the results returned by an <i>ignore</i> extraction rule. Allowed values: <code>true</code> , <code>false</code> .	true
<i>enrichment_extracts.meta.classification</i>	string — This value is defined in Rules by selecting appropriate options under Action and Confidence . Allowed classification metadata values are <code>good</code> , <code>bad</code> , and <code>unknown</code> .	good

Field	Description	Example
<i>enrichment_extracts.meta.confidence</i>	string — This value is defined in Rules by selecting the appropriate option under Action and Confidence . The selected action must be Mark as malicious for the Confidence drop-down list to become available. Allowed confidence metadata values are <code>low</code> , <code>medium</code> , and <code>high</code> .	<code>high</code>
<i>enrichment_extracts.value</i>	string — The actual value of the enrichment observable, based on the enrichment observable data type.	<code>doom.dismay.biz</code>

For reference, you can look up a complete list of all available search query fields in Kibana:

- To access Kibana, in the web browser address bar enter a URL with the following format:
https://<platform_host>/api/kibana/app/kibana#/
 Keep the trailing */*
 Example: *https://platform.host.com/api/kibana/app/kibana#/*
- Select the **stix** index field:



- On the main menu bar, select **Settings**:

Discover
Visualize
Dashboard
Settings

Indices
Advanced
Objects
About

Index Patterns
+ Add New

- ★ logstash-*
- statsd-*
- stix

stix

★
↻
🗑️

This page lists every field in the stix index and the field's associated core type as recorded by Elasticsearch. While this list allows you to view the core type of each field, changing field types must be done using Elasticsearch's [Mapping API](#)

Fields (428)

Scripted fields (0)

name ↕	type ↕	format ↕	analyzed ⓘ ↕	indexed ⓘ ↕	controls
data.kill_chain_phases.kill_chain_name	string		✓	✓	
data.observable.object.related_objects.related_objects.relationship	string		✓	✓	
data.observable.composition.composition.composition.type	string		✓	✓	
data.producer.contributing_sources.type	string		✓	✓	
data.observable.object.related_objects.related_objects.properties_xml_type	string		✓	✓	
exposure.affected_overrides.state	boolean			✓	
data.test_mechanisms.rules.value	string		✓	✓	
data.indicated_ttps.idref	string		✓	✓	
data.handling.marking_structures.marking_structure_type	string		✓	✓	
exposure.sighted	boolean			✓	
exposure.prevent_ok	boolean			✓	
destinations	string			✓	
tags	string		✓	✓	

Cisco Threat Grid integration

Integrate EclecticIQ Platform with Cisco Threat Grid through the Threat Grid API. You can implement the integration as an incoming feed to ingest entities, as well as an enricher to produce enrichment observables that augment entity intel value.

Cisco Threat Grid	integration
Integration	Cisco Threat Grid
Type	enricher, incoming feed
API endpoint	<code>https://panacea.threatgrid.com/api/v2/</code>
Input	domain, hash-md5, hash-sha1, hash-sha256, hash-sha512, host, ipv4, ipv6, uri, winregistry
Output	Indicators with embedded observables representing IOCs (integration as incoming feed). Enriches supported observable types, as well as all found observables based on the enricher configuration, with information such as IP addresses, domains, host names, hashes, and Windows registry keys. (integration as enricher).
Description	Polls data from the Cisco Threat Grid API. It provides information on a range of cyber threat data like IP addresses, domains, registry keys, network streams, and hash files.

EclecticIQ Platform integrates with Cisco Threat Grid to use it as an intel provider. The platform integrates with the Cisco Threat Grid API in the following ways:

- By configuring the Threat Grid API as an incoming feed intel provider.
When it is configured as an incoming feed, the Cisco Threat Grid integration provides data that is ingested and stored as entities.
- By configuring the Threat Grid API as an enricher.
When it is configured as an enricher, the Cisco Threat Grid integration provides enrichment data that produces entity observables.

Configure Cisco Threat Grid as an incoming feed

Configure the general options

✓ Input fields marked with an asterisk are required.

The **Incoming feeds** page displays an overview of the configured incoming feeds ingesting data from the specified intel providers and data sources.

- On the top navigation bar, select **Data configuration > Incoming feeds**.

- On the top-left corner of the page click the **+** icon to open the incoming feed editor.
- On the **Create incoming feed** form you can populate the input fields to define the intel provider/data source for the feed, and the feed behavior.
- Under **Feed name**, enter a name for the feed you are creating. It should be descriptive and easy to remember.
- Under **Organization**, enter a name for the organization that serves as the intel provider for the incoming feed.
- Use **Source reliability** to flag the incoming feed with a value from the drop-down list to help other users assess how trustworthy the feed source is deemed to be.
This value has the same meaning as the first character in the **two-character Admiralty System code** (https://en.wikipedia.org/wiki/admiralty_code).
- **Require valid signature**: select this checkbox to enforce PGP signature validation of the incoming feed data.
To work correctly, the source data provider needs to offer a PGP validation service based on a public and a private key.
Moreover, you need to obtain a valid PGP public key from the source data provider, which you need to add to the platform trusted keys.
To add a trusted key to the platform, do the following::
 - On the left-hand navigation sidebar click **⚙ > System settings > Trusted keys > Edit settings** .
 - On the **Edit public trusted keys settings** page, click **+ Add** or **+ More** to add a new PGP public key:
 - **Key**: copy-paste into this field the public PGP key you want to add as a trusted key to verify the PGP signature of incoming data packages, including the `-----BEGIN PGP PUBLIC KEY BLOCK-----` and `-----END PGP PUBLIC KEY BLOCK-----` lines.
 - **Description**: add a short description to help users understand the purpose of the PGP public key.
 - Click **Save** to store your changes, or **Cancel** to discard them.
- **Skip extraction of observables from unstructured text**: select this checkbox to exclude from ingestion observable data detected in unstructured text sections.
If you select the checkbox, the platform filters out any observable data detected inside titles, headers, descriptions, summaries, and other free-form, free text fields.
Observable data inside unstructured text fields is usually not as relevant, and not as valuable in terms of intelligence, as observable data extracted from, for example, CybOX objects and fields.
- From the **Transport type** drop-down menu select **ThreatGRID API**.

Configure the transport type

Cisco Threat Grid API

Set a schedule

Under **Execution schedule** you can define how often you want to run the feed task:

- **None**: scheduled feed execution is disabled. You need to manually trigger the task to ingest or to publish data through an incoming or an outgoing feed, respectively.

- **Every [n] minutes:** the feed task runs automatically once every [n] minutes, where [n] defines the selected time interval in minutes.
You define the execution interval in 5-minute increments from the corresponding drop-down menu.
- **Every hour, [n] minutes past the hour:** the feed task runs automatically once an hour every hour at the specified minute offset from the hour.
You define how long in minutes after the beginning of an hour the task should run from the corresponding drop-down menu.
- **Every [n] hours:** the feed task runs automatically once every [n] hours, where [n] defines the time interval in hours between two consecutive feed task runs.
You define how long the time interval between feed executions should be by selecting the number of hours from the corresponding drop-down menu.
- **Every day at [time]:** the feed task runs automatically once a day at the specified time.
You define the time of the day when the task should run from the corresponding drop-down menus.
- **Every [n] days:** the feed task runs automatically once every [n] days, where [n] defines the time interval in days between two consecutive feed task runs.
You define how long the time interval between feed executions should be by selecting the number of days from the corresponding drop-down menu.
- **Every week on [day of the week] at [time]:** the feed task runs automatically once a week on the designated day, at the specified time.
You define the day of the week and time of the day when the task should run from the corresponding drop-down menus.
- **Every month on [day of the month] at [time]:** the feed task runs automatically once a month on the designated day of the month, at the specified time.
You define the day of the week and time of the day when the task should run from the corresponding drop-down menus.
Keep in mind that not all months of the year have 30 or 31 days.

Set a TLP override

Override TLP overwrites the **TLP** (<https://www.us-cert.gov/tlp>) color code associated with the feed entities with the one you set here. The selected TLP value is assigned to all the entities in the feed.

You can override the original or the current TLP color code of an entity, an incoming feed, or an outgoing feed.

When working as a filter, TLP colors select a decreasing range: if you set a TLP color as a filter the enricher, the feed, or the returned filtered results include all the entities flagged with the selected TLP color code, as well as all the entities whose TLP color indicates that they are progressively lower risk, less sensitive, and suitable for disclosure to broader audiences.

For example, if you select green the filtered results include entities with a TLP color set to green, as well as entities with a TLP color set to white, and entities with no TLP color code flag.

Set half-life values

It represents the amount of time it takes an entity to lose half its intelligence value.

It corresponds to the number of days it takes the intelligence value of a malicious entity to decay by 50%.

When configuring an incoming or an outgoing feed, you can set a half-life value in days for the following entity properties:

- **Campaign**
- **Course of action**
- **Exploit target**
- **Incident**
- **Indicator**
- **TTP**
- **Threat actor**
- **Report**

To set a half-life for one or more of these properties, do the following::

- Enter a numerical value in the entity property input field(s) you want to flag with a half-life value in days.
- Click **Save** to store your changes, or **Cancel** to discard them.

Save options

Besides committing current data by clicking **Save**, you can also click the downward-pointing arrow on the **Save** button to display a context menu with additional save options:

- **Save and new**: saves the current data for the active item, and it allows you to start creating a new item of the same type right away. For example, a dataset, a feed, a rule, a workspace, or a task.
- **Save and duplicate**: saves the current data for the active item, and it creates a pre-populated copy of the same item, which you can use as a template to speed up manual creation work.

Configure Cisco Threat Grid as an enricher

Enrichment rules and enrichment tasks drive the enrichment process to:

- Poll selected and trustworthy intelligence data sources;
- Retrieve relevant, accurate, and reliable data to augment platform entities with additional bits of information that provide additional context.

Rules

Enrichment rules define what to do with the retrieved enrichment data.

Rules act like filters, and they set the logical constraints defining:

- The platform data sources to augment with enrichment information.
Data sources you can enrich are incoming feeds, other enrichers, and groups.
- Within the selected platform data sources, the entity type(s) to augment with enrichment information.
- The enrichers to use to fetch enrichment data.

Tasks

Enrichment tasks define process execution by setting the following options:

- The data fetching mechanism — for example, an API endpoint exposing the enrichment data service.
- Specific data sources — for example, datasets targeting threat actors like hackers and terrorist groups.
- Data rate limit and monthly execution cap values to control the amount of polled data.

- A source reliability flag for the incoming enrichment data to simplify assessing the quality of the retrieved data.

Observables

Observables augment the entities they are related to by providing additional context that can help discover indirect relationships or spawn new relationships between entities.

Observables are atomic and factual: an observable represents one discrete piece of information that describes a fact. For example, an IP address, a hash value, the name of a location or an actor.

Configure enricher tasks

To configure or to edit an enricher task, do the following:

- On the top navigation bar click **Data configuration > Enrichers**.
- On the enricher overview page click the tile corresponding to the enricher you want to configure or modify.
- On the enricher detail page click the **Edit** button.

✓ Input fields marked with an asterisk are required.

- **Observable types:** select one or more observable types you want to enrich with data retrieved through the Cisco Threat Grid enricher.

Supported observable types:

- *domain*
- *hash-md5*
- *hash-sha1*
- *hash-sha256*
- *hash-sha512*
- *host*
- *ipv4*
- *ipv6*
- *uri*
- *winregistry*

Under **Parameters**, define the specific configuration options for the Cisco Threat Grid enricher:

- **API URL:** the URL pointing to the API endpoint exposing the service that grants access to the enricher data source. Contact the intel provider to subscribe to the service and to obtain this information, as well as any required authentication and authorization credentials.
- **API key:** contact Cisco to receive an API key, and then enter it in the corresponding input field.
- **Organization only:** select this checkbox to enable the enricher to check and display only submitted samples created by the organization the current user belongs to. That is, the organization needs to be the author of the submitted samples. When selected, this field is validated against the API key value granting access to the service.

- **Max low confidence threat score** : you can set an *upper threshold* to automatically flag enriched observables with a *low confidence* value.
After completing the sample analysis, enriched observables with a *lower* threat score than the specified value are flagged as **Malicious - Low confidence**.
 - Enter an integer value between 0 and 100.
 - Default value: 85.
- **Min high confidence threat score** : you can set a *bottom threshold* to automatically flag enriched observables with *high confidence* value.
After completing the sample analysis, enriched observables with a *higher* threat score than the specified value are flagged as **Malicious - High confidence**.
 - Enter an integer value between 0 and 100.
 - Default value: 95.
- Enriched observables with a threat score falling in the range defined by **Max low confidence threat score** (range lower limit) and **Min high confidence threat score** (range upper limit) are flagged as **Malicious - Medium confidence**.
- Click **Save** to store your changes, or **Cancel** to discard them.

Configure enricher rules

Add enricher rules

To add a new enricher rule, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment** .
- The **Rules > Enrichment** page shows an overview of the configured enricher rules.
You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.
- Click the + icon.

✓ Input fields marked with an asterisk are required.

On the **Create enrichment rule** page, fill out the fields to create the new enricher rule:

- **Name**: define a name to identify the rule. It should be descriptive and easy to remember.
- **Description**: additional textual details. If you want, you can add a short description to provide more information and context.
- Click **+ Add** or **+ More** to add a filtering option.
- **Source**: from the drop-down menu select the incoming feed, enricher, or group whose entities and observables you want to augment with additional information.
- **Entity types**: from the drop-down menu select the entity types you want to enrich with additional information.
- **TLP**: from the drop-down menu select the TLP color code you want to use to filter enrichment data.
TLP (<https://www.us-cert.gov/tlp>) provides an intuitive reference to assess how sensitive information is, focusing in particular on how serious it is, and whom it should or should not be shared with.

- Click **+** **Add** or **+** **More** to add a new filtering option. For example, to include another incoming feed or a different entity type. A filter can take only one source and one entity type at a time, but you can set up rules with as many filters as you need.
- **Enrichers**: from the drop-down menu select one or more enrichers to apply the rule to. When a rule is applied to one or more enrichers, it filters the enrichment data polled from the enricher source, based on the specified rule filters and criteria.
- Select the **Enabled** checkbox to enable the rule immediately after creating it.
- Click **Save** to store your changes, or **Cancel** to discard them.

Save options

Besides committing current data by clicking **Save**, you can also click the downward-pointing arrow on the **Save** button to display a context menu with additional save options:

- **Save and new**: saves the current data for the active item, and it allows you to start creating a new item of the same type right away. For example, a dataset, a feed, a rule, a workspace, or a task.
- **Save and duplicate**: saves the current data for the active item, and it creates a pre-populated copy of the same item, which you can use as a template to speed up manual creation work.

Edit enricher rules

To edit enricher rules, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment**.
- The **Rules > Enrichment** page shows an overview of the configured enricher rules. You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.

To edit the details of a specific rule, do the following:

- Click an area on the row corresponding to the rule you want to examine. An overlay slides in from the side of the screen to display the rule detail pane.
- On the rule detail pane click **Actions > Edit**.

Alternatively:

- Click the  icon on the row corresponding to the enricher you want to configure or modify.
- From the drop-down menu select **Edit**.

 Input fields marked with an asterisk are required.

- **Name**: define a name to identify the rule. It should be descriptive and easy to remember.
- **Description**: additional textual details. If you want, you can add a short description to provide more information and context.
- **Source**: from the drop-down menu select the incoming feed, enricher, or group whose entities and observables you want to augment with additional information.
- **Entity types**: from the drop-down menu select the entity types you want to enrich with additional information.

- **TLP:** from the drop-down menu select the TLP color code you want to use to filter enrichment data. **TLP** (<https://www.us-cert.gov/tlp>) provides an intuitive reference to assess how sensitive information is, focusing in particular on how serious it is, and whom it should or should not be shared with.
- Click **+ Add** or **+ More** to add a new filtering option. For example, to include another incoming feed or a different entity type.
- **Enrichers:** from the drop-down menu select one or more enrichers to apply the rule to. They are external data providers that are polled to obtain relevant enricher raw data; for example, whois lookup, reverse DNS, or GeolIP information.
- Select the **Enabled** checkbox to enable the rule immediately after creating it.
- Click **Save** to store your changes, or **Cancel** to discard them.

Delete enricher rules

To delete an enricher rule, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment**.
- The **Rules > Enrichment** page shows an overview of the configured enricher rules. You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.

To delete a specific rule, do the following:

- Click an area on the row corresponding to the rule you want to delete. An overlay slides in from the side of the screen to display the rule detail pane.
- On the rule detail pane click **Actions > Delete**.

Alternatively:

- Click the  icon on the row corresponding to the rule you want to delete.
- From the drop-down menu select **Delete**.
- On the confirmation pop-up dialog, click **Delete** to confirm the action.
- The rule is deleted.

Run the enricher

Automatically

To automatically enrich entities, make sure enricher tasks are active, and the necessary enrichment rules are configured.

Rules give you control over the type of information you want to retrieve or exclude, and what you want to do with it. You can assign one or more enricher sources to specific observable types. You can set multiple filters to cover usage scenarios as needed. You can then examine the returned enrichment observable data, as well as route it to other devices that enforce cyber threat detection or prevention.


To run the enricher automatically, go to the enricher edit mode, and make sure the **Enabled** checkbox on the edit form is selected.

If it is deselected, check it, and then click **Save**.

Manually

To adjust enrichment behavior to manually apply it to the entities you want to enrich, do the following:

- Open an entity in edit mode.
For example, on the top navigation bar click **Browse > Published** to display an overview of the published entities available in the platform.
- On the row corresponding to the entity you want to manually enrich, click the  icon to display the context menu.
- From the drop-down menu select **Edit**.
- At the bottom of the entity editor page click the **Manually enrich** checkbox.
A new input field with a drop-down menu becomes available.
- From the drop-down menu select one or more enrichers you want to apply to the entity.



Workflow

Add to dataset

Manually enrich

Enrichers to apply

Please select one or more options ▼

- Select all options
- CVE Search enricher
- Censys Enricher
- Circl.lu IP's related to SSL Certificate
- Circl.lu SSL Certificate Fetcher

CANCEL SAVE DRAFT PUBLISH

- Click **Save draft** to store your changes without publishing the entity, **Publish** to release the new version of the entity including your changes, or **Cancel** to discard the changes.

Alternatively, you can manually enrich an entity by selecting it; for example, from a dataset, from **Browse** or from **Discovery**.

An overlay slides in from the side of the screen to display the entity detail pane.

- On the entity detail pane, click **Observables**.
- The **Observables** tab shows an overview of the enrichment observables the entity has been augmented with.

To manually enrich the entity observables:

- Click the  refresh icon to trigger a task run that polls all the enrichers configured for the entity.

Alternatively:

- From the **Actions** pop-up menu, select **Enrich > Enrich with all**.
- The platform polls all applicable enrichers for the entity, and it enriches all the entity observables with the retrieved data.

✕ Malicious files detected

Ingested: 06.10.2017 9:20 Incoming feed: TAXII Stand Samples TLP Not Set

OVERVIEW OBSERVABLES NEIGHBORHOOD JSON VERSIONS HISTORY

☰ | + ☰

<input type="checkbox"/>	Type ✓ Value	Relation	Sighted	Conn.	First seen	Maliciousness	🔄
<input type="checkbox"/>	hash-sha256: e3b0c44298fc1c149afb4c899...	Related +1		2	06.10.2017 9:20	●	⋮
<input type="checkbox"/>	hash-sha256: d7a8fbb307d7809469ca9abc...	Related +1		1	06.10.2017 9:20	●	⋮
<input type="checkbox"/>	file: readme.doc.exe	Related +1		1	06.10.2017 9:20	●	⋮

Edit

Delete

Add to dataset

Add to graph

Create task

Export >

Download original

Enrich >

Enrich with all (5)

Censys Enricher

CrowdStrike Enricher

FireEye

Flashpoint AggregINT Enricher

Flashpoint Thresher Enricher

To poll a specific enricher:

- From the **Actions** pop-up menu, select **Enrich**, and then click the specific enricher whose task run you want to trigger.
- The platform polls the specified enricher for the entity, and it enriches all supported entity observables with the retrieved data.

✕ Malicious files detected

★
Ingested: 06.10.2017 9:20 Incoming feed: TAXII Stand Samples
● TLP Not Set

OVERVIEW
OBSERVABLES
NEIGHBORHOOD
JSON
VERSIONS
HISTORY

✕ 3 selected
Deselect all

Enrich ▾

Add to ▾

⋮

<input checked="" type="checkbox"/>	Type Value	Relation	Sighted	Conn.	
<input checked="" type="checkbox"/>	hash-sha256: e3b0c44298fc1c149afb4c899...	Related +1		2	Enrich with all (5)
<input checked="" type="checkbox"/>	hash-sha256: d7a8fbb307d7809469ca9abc...	Related +1		1	Censys Enricher
<input checked="" type="checkbox"/>	file: readme.doc.exe	Related +1		1	CrowdStrike Enricher
					FireEye
					Flashpoint AggregINT Enricher
					Flashpoint Thresher Enricher

To enrich only specific observables:

- On the **Observables** tab, select the checkboxes corresponding to the observables you want to enrich.
- From the **Enrich** drop-down menu, select **Enrich with all**.
- The platform polls all applicable enrichers for the entity, and it enriches the selected entity observables with the retrieved data.

✕ Malicious files detected

★
Ingested: 06.10.2017 9:20 Incoming feed: TAXII Stand Samples
● TLP Not Set

OVERVIEW
OBSERVABLES
NEIGHBORHOOD
JSON
VERSIONS
HISTORY

✕ 2 selected
Deselect all

Enrich ▾

Add to ▾

⋮

<input type="checkbox"/>	Type Value	Relation	Sighted	Conn.	
<input checked="" type="checkbox"/>	hash-sha256: e3b0c44298fc1c149afb4c899...	Related +1		2	Enrich with all (5)
<input type="checkbox"/>	hash-sha256: d7a8fbb307d7809469ca9abc...	Related +1		1	Censys Enricher
<input checked="" type="checkbox"/>	file: readme.doc.exe	Related +1		1	CrowdStrike Enricher
					FireEye
					Flashpoint AggregINT Enricher
					Flashpoint Thresher Enricher

The available enricher tasks in the drop-down menu are automatically filtered to show only the applicable enrichers for the entity.

Enrichers automatically augment all the entities that accept the enricher's content type as an observable. In other words, the observable types an entity supports define the applicable enrichers an entity can use.

Review enrichment observables

The Cisco Threat Grid enricher can take the following observable types as input:

- *domain, hash-md5, hash-sha1, hash-sha256, hash-sha512, host, ipv4, ipv6, uri, winregistry*

The enricher uses these input data types to look for additional information to enrich existing observables with. Any entity types supporting these observable types can be enriched with Cisco Threat Grid.

To view enrichment information on the entity detail pane, do the following:

- Select an entity; for example, from a dataset, from **Browse** or from **Discovery**. An overlay slides in from the side of the screen to display the entity detail pane.
- On the entity detail pane, click **Observables**.
- The **Observables** tab shows an overview of the enrichment observables the entity has been augmented with.

Ingested: Yesterday at 23:59 Incoming feed: tor ○ TLP White

OVERVIEW **OBSERVABLES** NEIGHBORHOOD JSON VERSIONS HISTORY

Add observable

<input type="checkbox"/> type / Value	Relation	Sighted	Conn.	First seen	Maliciousness	
<input type="checkbox"/> domain: torstatus.blutmagie.de	Description + 1		96264	02.08.2017 14:52	●●●	⋮
<input type="checkbox"/> ipv4: 194.63.141.179	OpenResolve + 4			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> email: registry@regfish.com	Threatcrowd AP...			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-md5: e63989f8df535a14cee4a06484c...	Recorded Future			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-sha256: c27c743c64713fd2a2b36b32...	Recorded Future			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-sha512: 5a9df660747757935abfcdf4...	Recorded Future			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> email: bitwisser@googlemail.com	Recorded Future			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-sha1: 4e0c92f8e8dca4d9295c7587e7...	Recorded Future			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-md5: b7532bac9c0d65b3a4a724a603...	Recorded Future			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-sha256: 6ae3032f45266fd48589bfa8...	Recorded Future			02.08.2017 14:53	●●●	⋮

1 - 10 of 123 |< < > >|


Review enrichment observables on the graph

To view enrichment data and their connections with other entities and observables on the graph, do the following:


- On the row corresponding to the observable you want to load on the graph, click the  icon, and then select **Add to graph**.

Type	Value	Sightings	Maliciousness	Connections	Source	Timestamp	
ipV4	217.93.38.31			1	tor	29.08.2017 9:23	
domain	pd95d261f.dip0.t-ipconnect.de			1	tor		Ignore observable Create indicator Create sighting Add to graph Set maliciousness >
ipV4	93.238.180.183			1	Gecko Indicator...		
hash-md5	961b27607e5c2f7915558e1cee520bb4			7	Gecko CS indic...		
uri	https://www.threathq.com/p42/search/default?m=7413			1	Gecko Phishme...		

- To load the parent entity whose detail pane you are viewing, instead of its observables, from the pop-up **Actions** menu at the bottom of the pane select **Add to graph**.
- Click the graph thumbnail on the lower side of the screen to expand it.
- On the graph, right-click the entity you want to inspect, and from the context menu select **Load entities > All**, **Load observables > All** or **Load entities by extract > All**.




- Right-click an extract or an entity for further inspection and from the context menu select **Load entities > All**, **Load observables > All** or **Load entities by extract > All**.




To see how entities, observables and enrichment observables are connected, and to inspect relationships between distant items, do the following:

- **CTRL + click** two nodes on the graph to select them.
- Right-click either selected node, and from the context menu select **Find path** to query the graph database about the existence of a path between the nodes, or **Show path** to highlight an existing path on the graph.
- If a path does exist, the selected nodes and all the intermediate ones are highlighted on the graph to show the path that links them.



Search for enrichment observables

You can use the search box to look for enrichment observables. You can find the search box on the top bar:




Enter search terms and search queries, and then press **ENTER** or click the search icon to run the search. Searches you run through this search box are executed platform-wide.

i The search functionality uses **Elasticsearch query syntax** (<https://www.elastic.co/guide/en/elasticsearch/reference/current/full-text-queries.html>).


To access a cheatsheet with search examples using entity types, filters, and for help with the search syntax, click **Help** to display thematic drop-down lists with common search queries:

- **Filters:** examples of quick search filters.

- **Help:** examples of regex, Boolean, wildcards, and tag search usage.
- **Entities:** examples of searchable entity types.



Besides full text search, you can use Boolean operators, wildcards, regex, and you can combine these filtering options to create more refined searches.



Use operators to combine multiple quick filters and create a more complex search query.

Example:


```
enrichment_extracts.kind:domain AND enrichment_extracts.meta.classification:high
```

Field	Description	Example
<i>enrichment_extracts.id</i>	string — The alphanumeric ID string that uniquely identifies the enrichment observable.	01h12x45-01q2-1234-od01-123456h78h90
<i>enrichment_extracts.kind</i>	string — The enrichment observable data type.	domain
<i>enrichment_extracts.meta.blacklisted</i>	Boolean — An observable is blacklisted when it is included in the results returned by an <i>ignore</i> extraction rule. Allowed values: <code>true</code> , <code>false</code> .	true
<i>enrichment_extracts.meta.classification</i>	string — This value is defined in Rules by selecting appropriate options under Action and Confidence . Allowed classification metadata values are <code>good</code> , <code>bad</code> , and <code>unknown</code> .	good

Field	Description	Example
<code>enrichment_extracts.meta.confidence</code>	string — This value is defined in Rules by selecting the appropriate option under Action and Confidence . The selected action must be Mark as malicious for the Confidence drop-down list to become available. Allowed confidence metadata values are <code>low</code> , <code>medium</code> , and <code>high</code> .	<code>high</code>
<code>enrichment_extracts.value</code>	string — The actual value of the enrichment observable, based on the enrichment observable data type.	<code>doom.dismay.biz</code>

For reference, you can look up a complete list of all available search query fields in Kibana:

- To access Kibana, in the web browser address bar enter a URL with the following format:
`https://<platform_host>/api/kibana/app/kibana#/`
 Keep the trailing `/`
 Example: `https://platform.host.com/api/kibana/app/kibana#/`
- Select the **stix** index field:



- On the main menu bar, select **Settings**:

Discover
Visualize
Dashboard
Settings

Indices
Advanced
Objects
About

Index Patterns
+ Add New

- ★ logstash-*
- statsd-*
- stix

stix

★
↻
🗑️

This page lists every field in the stix index and the field's associated core type as recorded by Elasticsearch. While this list allows you to view the core type of each field, changing field types must be done using Elasticsearch's [Mapping API](#)

Fields (428)

Scripted fields (0)

name ↕	type ↕	format ↕	analyzed ⓘ ↕	indexed ⓘ ↕	controls
data.kill_chain_phases.kill_chain_name	string		✓	✓	✎
data.observable.object.related_objects.related_objects.relationship	string		✓	✓	✎
data.observable.composition.composition.composition.type	string		✓	✓	✎
data.producer.contributing_sources.type	string		✓	✓	✎
data.observable.object.related_objects.related_objects.properties_xml_type	string		✓	✓	✎
exposure.affected_overrides.state	boolean			✓	✎
data.test_mechanisms.rules.value	string		✓	✓	✎
data.indicated_ttps.idref	string		✓	✓	✎
data.handling.marking_structures.marking_structure_type	string		✓	✓	✎
exposure.sighted	boolean			✓	✎
exposure.prevent_ok	boolean			✓	✎
destinations	string			✓	✎
tags	string		✓	✓	✎

Flashpoint integration

Integrate EclecticIQ Platform with Flashpoint AggregINT, Flashpoint Blueprint, and Flashpoint Thresher through the Flashpoint API.

Configure the enrichers

Enrichment rules and enrichment tasks drive the enrichment process to:

- Poll selected and trustworthy intelligence data sources;
- Retrieve relevant, accurate, and reliable data to augment platform entities with additional bits of information that provide additional context.

Rules

Enrichment rules define what to do with the retrieved enrichment data. Rules act like filters, and they set the logical constraints defining:

- The platform data sources to augment with enrichment information. Data sources you can enrich are incoming feeds, other enrichers, and groups.
- Within the selected platform data sources, the entity type(s) to augment with enrichment information.
- The enrichers to use to fetch enrichment data.

Tasks

Enrichment tasks define process execution by setting the following options:

- The data fetching mechanism — for example, an API endpoint exposing the enrichment data service.
- Specific data sources — for example, datasets targeting threat actors like hackers and terrorist groups.
- Data rate limit and monthly execution cap values to control the amount of polled data.
- A source reliability flag for the incoming enrichment data to simplify assessing the quality of the retrieved data.

Observables

Observables augment the entities they are related to by providing additional context that can help discover indirect relationships or spawn new relationships between entities.

Observables are atomic and factual: an observable represents one discrete piece of information that describes a fact. For example, an IP address, a hash value, the name of a location or an actor.

The Flashpoint AggregINT, Flashpoint Blueprint, and Flashpoint Thresher enrichers share almost identical configuration options, the only differences being the number and the type of available Flashpoint datasets per enricher.

Configure enricher tasks

To configure or to edit an enricher task, do the following:

- On the top navigation bar click **Data configuration > Enrichers**.

- On the enricher overview page click the tile corresponding to the enricher you want to configure or modify.
- On the enricher detail page click the **Edit** button.

✓ Input fields marked with an asterisk are required.

- **Name:** the name used to identify the enricher. It should be descriptive and easy to remember.
- **Description:** additional textual details. If you want, you can add a short description to provide more information and context.
- **Cache validity (sec):** defines for how long enrichment data remains stored in the cache. The value is expressed in seconds.
- **Rate limit (per sec):** sets the maximum allowed number of requests/executions per second.
- **Monthly execution cap (executions):** sets a maximum allowed number of requests/executions per month. Together with rate limiting, execution cap helps control data traffic for the enricher; for example, when the API or the service you are connecting to enforces usage limits.
- **Source reliability:** from the drop-down menu select an option to flag the feed or enricher content with a predefined reliability value to help other users assess how trustworthy the data source is. Values in this menu have the same meaning as the first character in the **two-character Admiralty System code** (https://en.wikipedia.org/wiki/admiralty_code).
Example: *B - Usually reliable*
- **Enabled:** checkbox. Select the **Enabled** checkbox to enable the enricher task immediately after editing and saving it. If you select the checkbox, the enricher or the rule is executed automatically. If you deselect it, you need to manually run the enricher or the rule.
- Under **Parameters**, define the specific configuration options for the selected enricher, where applicable.
- Click **Save** to store your changes, or **Cancel** to discard them.

Configure enricher rules

Add enricher rules

To add a new enricher rule, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment**.
- The **Rules > Enrichment** page shows an overview of the configured enricher rules. You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.
- Click the + icon.

✓ Input fields marked with an asterisk are required.

On the **Create enrichment rule** page, fill out the fields to create the new enricher rule:

- **Name:** define a name to identify the rule. It should be descriptive and easy to remember.
- **Description:** additional textual details. If you want, you can add a short description to provide more information and context.
- Click **+ Add** or **+ More** to add a filtering option.
- **Source:** from the drop-down menu select the incoming feed, enricher, or group whose entities and observables you want to augment with additional information.
- **Entity types:** from the drop-down menu select the entity types you want to enrich with additional information.
- **TLP:** from the drop-down menu select the TLP color code you want to use to filter enrichment data.
TLP (<https://www.us-cert.gov/tlp>) provides an intuitive reference to assess how sensitive information is, focusing in particular on how serious it is, and whom it should or should not be shared with.
- Click **+ Add** or **+ More** to add a new filtering option. For example, to include another incoming feed or a different entity type. A filter can take only one source and one entity type at a time, but you can set up rules with as many filters as you need.
- **Enrichers:** from the drop-down menu select one or more enrichers to apply the rule to.
When a rule is applied to one or more enrichers, it filters the enrichment data polled from the enricher source, based on the specified rule filters and criteria.
- Select the **Enabled** checkbox to enable the rule immediately after creating it.
- Click **Save** to store your changes, or **Cancel** to discard them.

Save options

Besides committing current data by clicking **Save**, you can also click the downward-pointing arrow on the **Save** button to display a context menu with additional save options:

- **Save and new:** saves the current data for the active item, and it allows you to start creating a new item of the same type right away. For example, a dataset, a feed, a rule, a workspace, or a task.
- **Save and duplicate:** saves the current data for the active item, and it creates a pre-populated copy of the same item, which you can use as a template to speed up manual creation work.

Edit enricher rules

To edit enricher rules, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment**.
- The **Rules > Enrichment** page shows an overview of the configured enricher rules.
You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.

To edit the details of a specific rule, do the following:

- Click an area on the row corresponding to the rule you want to examine. An overlay slides in from the side of the screen to display the rule detail pane.
- On the rule detail pane click **Actions > Edit**.

Alternatively:

- Click the  icon on the row corresponding to the enricher you want to configure or modify.

- From the drop-down menu select **Edit**.

✓ Input fields marked with an asterisk are required.

- **Name**: define a name to identify the rule. It should be descriptive and easy to remember.
- **Description**: additional textual details. If you want, you can add a short description to provide more information and context.
- **Source**: from the drop-down menu select the incoming feed, enricher, or group whose entities and observables you want to augment with additional information.
- **Entity types**: from the drop-down menu select the entity types you want to enrich with additional information.
- **TLP**: from the drop-down menu select the TLP color code you want to use to filter enrichment data. **TLP** (<https://www.us-cert.gov/tlp>) provides an intuitive reference to assess how sensitive information is, focusing in particular on how serious it is, and whom it should or should not be shared with.
- Click **+ Add** or **+ More** to add a new filtering option. For example, to include another incoming feed or a different entity type.
- **Enrichers**: from the drop-down menu select one or more enrichers to apply the rule to. They are external data providers that are polled to obtain relevant enricher raw data; for example, whois lookup, reverse DNS, or GeoIP information.
- Select the **Enabled** checkbox to enable the rule immediately after creating it.
- Click **Save** to store your changes, or **Cancel** to discard them.

Delete enricher rules

To delete an enricher rule, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment**.
- The **Rules > Enrichment** page shows an overview of the configured enricher rules. You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.

To delete a specific rule, do the following:

- Click an area on the row corresponding to the rule you want to delete. An overlay slides in from the side of the screen to display the rule detail pane.
- On the rule detail pane click **Actions > Delete**.

Alternatively:

- Click the  icon on the row corresponding to the rule you want to delete.
- From the drop-down menu select **Delete**.
- On the confirmation pop-up dialog, click **Delete** to confirm the action.
- The rule is deleted.

Run the enricher

Automatically

To automatically enrich entities, make sure enricher tasks are active, and the necessary enrichment rules are configured.

Rules give you control over the type of information you want to retrieve or exclude, and what you want to do with it. You can assign one or more enricher sources to specific observable types. You can set multiple filters to cover usage scenarios as needed. You can then examine the returned enrichment observable data, as well as route it to other devices that enforce cyber threat detection or prevention.

To run the enricher automatically, go to the enricher edit mode, and make sure the **Enabled** checkbox on the edit form is selected.

If it is deselected, check it, and then click **Save**.

Manually

To adjust enrichment behavior to manually apply it to the entities you want to enrich, do the following:

- Open an entity in edit mode.
For example, on the top navigation bar click **Browse > Published** to display an overview of the published entities available in the platform.
- On the row corresponding to the entity you want to manually enrich, click the  icon to display the context menu.
- From the drop-down menu select **Edit**.
- At the bottom of the entity editor page click the **Manually enrich** checkbox.
A new input field with a drop-down menu becomes available.
- From the drop-down menu select one or more enrichers you want to apply to the entity.

Workflow

Add to dataset

Manually enrich

Enrichers to apply

Please select one or more options

- Select all options
- CVE Search enricher
- Censys Enricher
- Circl.lu IP's related to SSL Certificate
- Circl.lu SSL Certificate Fetcher

CANCEL SAVE DRAFT PUBLISH

- Click **Save draft** to store your changes without publishing the entity, **Publish** to release the new version of the entity including your changes, or **Cancel** to discard the changes.

Alternatively, you can manually enrich an entity by selecting it; for example, from a dataset, from **Browse** or from **Discovery**.

An overlay slides in from the side of the screen to display the entity detail pane.

- On the entity detail pane, click **Observables**.
- The **Observables** tab shows an overview of the enrichment observables the entity has been augmented with.

To manually enrich the entity observables:

- Click the  refresh icon to trigger a task run that polls all the enrichers configured for the entity.

Alternatively:

- From the **Actions** pop-up menu, select **Enrich > Enrich with all**.
- The platform polls all applicable enrichers for the entity, and it enriches all the entity observables with the retrieved data.

✕ Malicious files detected

Ingested: 06.10.2017 9:20 Incoming feed: TAXII Stand Samples TLP Not Set

OVERVIEW OBSERVABLES NEIGHBORHOOD JSON VERSIONS HISTORY

☰ | + ☰

<input type="checkbox"/>	Type ✓ Value	Relation	Sighted	Conn.	First seen	Maliciousness	🔄
<input type="checkbox"/>	hash-sha256: e3b0c44298fc1c149afb4c899...	Related +1		2	06.10.2017 9:20	●	⋮
<input type="checkbox"/>	hash-sha256: d7a8fbb307d7809469ca9abc...	Related +1		1	06.10.2017 9:20	●	⋮
<input type="checkbox"/>	file: readme.doc.exe	Related +1		1	06.10.2017 9:20	●	⋮

Edit

Delete

Add to dataset

Add to graph

Create task

Export >

Download original

Enrich >

Enrich with all (5)

Censys Enricher

CrowdStrike Enricher

FireEye

Flashpoint AggregINT Enricher

Flashpoint Thresher Enricher

To poll a specific enricher:

- From the **Actions** pop-up menu, select **Enrich**, and then click the specific enricher whose task run you want to trigger.
- The platform polls the specified enricher for the entity, and it enriches all supported entity observables with the retrieved data.

Malicious files detected

Ingested: 06.10.2017 9:20 Incoming feed: TAXII Stand Samples TLP Not Set

OVERVIEW OBSERVABLES NEIGHBORHOOD JSON VERSIONS HISTORY

3 selected Deselect all Enrich Add to

Type	Value	Relation	Sighted	Conn.	Business
<input checked="" type="checkbox"/>	hash-sha256: e3b0c44298fc1c149afb4c899...	Related +1		2	
<input checked="" type="checkbox"/>	hash-sha256: d7a8fbb307d7809469ca9abcb...	Related +1		1	
<input checked="" type="checkbox"/>	file: readme.doc.exe	Related +1		1	

Enrich with all (5)
Censys Enricher
CrowdStrike Enricher
FireEye
Flashpoint AggregINT Enricher
Flashpoint Thresher Enricher

To enrich only specific observables:

- On the **Observables** tab, select the checkboxes corresponding to the observables you want to enrich.
- From the **Enrich** drop-down menu, select **Enrich with all**.
- The platform polls all applicable enrichers for the entity, and it enriches the selected entity observables with the retrieved data.

Malicious files detected

Ingested: 06.10.2017 9:20 Incoming feed: TAXII Stand Samples TLP Not Set

OVERVIEW OBSERVABLES NEIGHBORHOOD JSON VERSIONS HISTORY

2 selected Deselect all Enrich Add to

Type	Value	Relation	Sighted	Conn.	Business
<input type="checkbox"/>	hash-sha256: e3b0c44298fc1c149afb4c899...	Related +1		2	
<input type="checkbox"/>	hash-sha256: d7a8fbb307d7809469ca9abcb...	Related +1		1	
<input checked="" type="checkbox"/>	file: readme.doc.exe	Related +1		1	

Enrich with all (5)
Censys Enricher
CrowdStrike Enricher
FireEye
Flashpoint AggregINT Enricher
Flashpoint Thresher Enricher

The available enricher tasks in the drop-down menu are automatically filtered to show only the applicable enrichers for the entity.

Enrichers automatically augment all the entities that accept the enricher's content type as an observable. In other words, the observable types an entity supports define the applicable enrichers an entity can use.

Review enrichment observables

Flashpoint enrichers can take the following observable types as input:

- *actor-id, domain, email, hash-md5, hash-sha1, hash-sha256, hash-sha512, host, ipv4, ipv6, uri*

The enrichers use these data types to look for additional information on observables. Any entity types supporting these observable types can be enriched with Flashpoint enrichers.

To view enrichment information on the entity detail pane, do the following:

- Select an entity; for example, from a dataset, from **Browse** or from **Discovery**. An overlay slides in from the side of the screen to display the entity detail pane.
- On the entity detail pane, click **Observables**.
- The **Observables** tab shows an overview of the enrichment observables the entity has been augmented with.

Ingested: Yesterday at 23:59 Incoming feed: tor ○ TLP White

OVERVIEW **OBSERVABLES** NEIGHBORHOOD JSON VERSIONS HISTORY

Add observable

type / Value	Relation	Sighted	Conn.	First seen	Maliciousness	
<input type="checkbox"/> domain: torstatus.blutmagie.de	Description + 1		96264	02.08.2017 14:52	●●●	⋮
<input type="checkbox"/> ipv4: 194.63.141.179	OpenResolve + 4			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> email: registry@regfish.com	Threatcrowd AP...			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-md5: e63989f8df535a14cee4a06484c...	Recorded Future			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-sha256: c27c743c64713fd2a2b36b32...	Recorded Future			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-sha512: 5a9df660747757935abfcdf4...	Recorded Future			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> email: bitwisser@googlemail.com	Recorded Future			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-sha1: 4e0c92f8e8dca4d9295c7587e7...	Recorded Future			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-md5: b7532bac9c0d65b3a4a724a603...	Recorded Future			02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-sha256: 6ae3032f45266fd48589bfa8...	Recorded Future			02.08.2017 14:53	●●●	⋮

1 - 10 of 123 |< < > >|


Review enrichment observables on the graph

To view enrichment data and their connections with other entities and observables on the graph, do the following:


- On the row corresponding to the observable you want to load on the graph, click the **⋮** icon, and then select **Add to graph**.

Type	Value	Sightings	Maliciousness	Connections	Source	Timestamp	
ipV4	217.93.38.31		●	1	tor	29.08.2017 9:23	
domain	pd95d261f.dip0.t-ipconnect.de		●●●	1	tor		Ignore observable Create indicator Create sighting Add to graph Set maliciousness >
ipV4	93.238.180.183		●	1	Gecko Indicator...		
hash-md5	961b27607e5c2f7915558e1cee520bb4		●●●	7	Gecko CS indic...		
uri	https://www.threathq.com/p42/search/default?m=7413		●	1	Gecko Phishme...		

- To load the parent entity whose detail pane you are viewing, instead of its observables, from the pop-up **Actions** menu at the bottom of the pane select **Add to graph**.
- Click the graph thumbnail on the lower side of the screen to expand it.
- On the graph, right-click the entity you want to inspect, and from the context menu select **Load entities > All**, **Load observables > All** or **Load entities by extract > All**.




- Right-click an extract or an entity for further inspection and from the context menu select **Load entities > All**, **Load observables > All** or **Load entities by extract > All**.




To see how entities, observables and enrichment observables are connected, and to inspect relationships between distant items, do the following:

- **CTRL + click** two nodes on the graph to select them.
- Right-click either selected node, and from the context menu select **Find path** to query the graph database about the existence of a path between the nodes, or **Show path** to highlight an existing path on the graph.
- If a path does exist, the selected nodes and all the intermediate ones are highlighted on the graph to show the path that links them.



Search for enrichment observables

You can use the search box to look for enrichment observables. You can find the search box on the top bar:



Enter search terms and search queries, and then press **ENTER** or click the search icon to run the search. Searches you run through this search box are executed platform-wide.




The search functionality uses **Elasticsearch query syntax**

(<https://www.elastic.co/guide/en/elasticsearch/reference/current/full-text-queries.html>).


To access a cheatsheet with search examples using entity types, filters, and for help with the search syntax, click **Help** to display thematic drop-down lists with common search queries:

- **Filters:** examples of quick search filters.

- **Help:** examples of regex, Boolean, wildcards, and tag search usage.
- **Entities:** examples of searchable entity types.



Besides full text search, you can use Boolean operators, wildcards, regex, and you can combine these filtering options to create more refined searches.



Use operators to combine multiple quick filters and create a more complex search query.

Example:


```
enrichment_extracts.kind:domain AND enrichment_extracts.meta.classification:high
```

Field	Description	Example
<i>enrichment_extracts.id</i>	string — The alphanumeric ID string that uniquely identifies the enrichment observable.	01h12x45-01q2-1234-od01-123456h78h90
<i>enrichment_extracts.kind</i>	string — The enrichment observable data type.	domain
<i>enrichment_extracts.meta.blacklisted</i>	Boolean — An observable is blacklisted when it is included in the results returned by an <i>ignore</i> extraction rule. Allowed values: <code>true</code> , <code>false</code> .	true
<i>enrichment_extracts.meta.classification</i>	string — This value is defined in Rules by selecting appropriate options under Action and Confidence . Allowed classification metadata values are <code>good</code> , <code>bad</code> , and <code>unknown</code> .	good

Field	Description	Example
<code>enrichment_extracts.meta.confidence</code>	string — This value is defined in Rules by selecting the appropriate option under Action and Confidence . The selected action must be Mark as malicious for the Confidence drop-down list to become available. Allowed confidence metadata values are <code>low</code> , <code>medium</code> , and <code>high</code> .	<code>high</code>
<code>enrichment_extracts.value</code>	string — The actual value of the enrichment observable, based on the enrichment observable data type.	<code>doom.dismay.biz</code>

For reference, you can look up a complete list of all available search query fields in Kibana:

- To access Kibana, in the web browser address bar enter a URL with the following format:
`https://<platform_host>/api/kibana/app/kibana#/`
 Keep the trailing `/`
 Example: `https://platform.host.com/api/kibana/app/kibana#/`
- Select the **stix** index field:



- On the main menu bar, select **Settings**:

Discover
Visualize
Dashboard
Settings

Indices
Advanced
Objects
About

Index Patterns
+ Add New

- ★ logstash-*
- statsd-*
- stix

stix

★
↻
✖

This page lists every field in the stix index and the field's associated core type as recorded by Elasticsearch. While this list allows you to view the core type of each field, changing field types must be done using Elasticsearch's [Mapping API](#)

Fields (428)

Scripted fields (0)

name ↕	type ↕	format ↕	analyzed ⓘ ↕	indexed ⓘ ↕	controls
data.kill_chain_phases.kill_chain_name	string		✓	✓	
data.observable.object.related_objects.related_objects.relationship	string		✓	✓	
data.observable.composition.composition.composition.type	string		✓	✓	
data.producer.contributing_sources.type	string		✓	✓	
data.observable.object.related_objects.related_objects.properties_xml_type	string		✓	✓	
exposure.affected_overrides.state	boolean			✓	
data.test_mechanisms.rules.value	string		✓	✓	
data.indicated_ttps.idref	string		✓	✓	
data.handling.marking_structures.marking_structure_type	string		✓	✓	
exposure.sighted	boolean			✓	
exposure.prevent_ok	boolean			✓	
destinations	string			✓	
tags	string		✓	✓	

PassiveTotal integration

Integrate EclecticIQ Platform with RiskIQ PassiveTotal to retrieve active/passive DNS, IP, domain, and malware information.

Configure the enrichers

Enrichment rules and enrichment tasks drive the enrichment process to:

- Poll selected and trustworthy intelligence data sources;
- Retrieve relevant, accurate, and reliable data to augment platform entities with additional bits of information that provide additional context.

Rules

Enrichment rules define what to do with the retrieved enrichment data. Rules act like filters, and they set the logical constraints defining:

- The platform data sources to augment with enrichment information. Data sources you can enrich are incoming feeds, other enrichers, and groups.
- Within the selected platform data sources, the entity type(s) to augment with enrichment information.
- The enrichers to use to fetch enrichment data.

Tasks

Enrichment tasks define process execution by setting the following options:

- The data fetching mechanism — for example, an API endpoint exposing the enrichment data service.
- Specific data sources — for example, datasets targeting threat actors like hackers and terrorist groups.
- Data rate limit and monthly execution cap values to control the amount of polled data.
- A source reliability flag for the incoming enrichment data to simplify assessing the quality of the retrieved data.

Observables

Observables augment the entities they are related to by providing additional context that can help discover indirect relationships or spawn new relationships between entities.

Observables are atomic and factual: an observable represents one discrete piece of information that describes a fact. For example, an IP address, a hash value, the name of a location or an actor.

The PassiveTotal Whois, PassiveTotal Passive DNS, PassiveTotal IP/Domain, and PassiveTotal Malware enrichers share almost identical configuration options, the only differences being the available PassiveTotal dataset types per enricher.

Configure enricher tasks

To configure or to edit an enricher task, do the following:

- On the top navigation bar click **Data configuration > Enrichers**.

- On the enricher overview page click the tile corresponding to the enricher you want to configure or modify.
- On the enricher detail page click the **Edit** button.

✓ Input fields marked with an asterisk are required.

- **Name:** the name used to identify the enricher. It should be descriptive and easy to remember.
- **Description:** additional textual details. If you want, you can add a short description to provide more information and context.
- **Cache validity (sec):** defines for how long enrichment data remains stored in the cache. The value is expressed in seconds.
- **Rate limit (per sec):** sets the maximum allowed number of requests/executions per second.
- **Monthly execution cap (executions):** sets a maximum allowed number of requests/executions per month. Together with rate limiting, execution cap helps control data traffic for the enricher; for example, when the API or the service you are connecting to enforces usage limits.
- **Source reliability:** from the drop-down menu select an option to flag the feed or enricher content with a predefined reliability value to help other users assess how trustworthy the data source is. Values in this menu have the same meaning as the first character in the **two-character Admiralty System code** (https://en.wikipedia.org/wiki/admiralty_code).
Example: *B - Usually reliable*
- **Enabled:** checkbox. Select the **Enabled** checkbox to enable the enricher task immediately after editing and saving it. If you select the checkbox, the enricher or the rule is executed automatically. If you deselect it, you need to manually run the enricher or the rule.
- Under **Parameters**, define the specific configuration options for the selected enricher, where applicable.
- Click **Save** to store your changes, or **Cancel** to discard them.

Configure enricher rules

Add enricher rules

To add a new enricher rule, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment**.
- The **Rules > Enrichment** page shows an overview of the configured enricher rules. You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.
- Click the + icon.

✓ Input fields marked with an asterisk are required.

On the **Create enrichment rule** page, fill out the fields to create the new enricher rule:

- **Name:** define a name to identify the rule. It should be descriptive and easy to remember.
- **Description:** additional textual details. If you want, you can add a short description to provide more information and context.
- Click **+ Add** or **+ More** to add a filtering option.
- **Source:** from the drop-down menu select the incoming feed, enricher, or group whose entities and observables you want to augment with additional information.
- **Entity types:** from the drop-down menu select the entity types you want to enrich with additional information.
- **TLP:** from the drop-down menu select the TLP color code you want to use to filter enrichment data.
TLP (<https://www.us-cert.gov/tlp>) provides an intuitive reference to assess how sensitive information is, focusing in particular on how serious it is, and whom it should or should not be shared with.
- Click **+ Add** or **+ More** to add a new filtering option. For example, to include another incoming feed or a different entity type. A filter can take only one source and one entity type at a time, but you can set up rules with as many filters as you need.
- **Enrichers:** from the drop-down menu select one or more enrichers to apply the rule to.
When a rule is applied to one or more enrichers, it filters the enrichment data polled from the enricher source, based on the specified rule filters and criteria.
- Select the **Enabled** checkbox to enable the rule immediately after creating it.
- Click **Save** to store your changes, or **Cancel** to discard them.

Save options

Besides committing current data by clicking **Save**, you can also click the downward-pointing arrow on the **Save** button to display a context menu with additional save options:

- **Save and new:** saves the current data for the active item, and it allows you to start creating a new item of the same type right away. For example, a dataset, a feed, a rule, a workspace, or a task.
- **Save and duplicate:** saves the current data for the active item, and it creates a pre-populated copy of the same item, which you can use as a template to speed up manual creation work.

Edit enricher rules

To edit enricher rules, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment**.
- The **Rules > Enrichment** page shows an overview of the configured enricher rules.
You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.

To edit the details of a specific rule, do the following:

- Click an area on the row corresponding to the rule you want to examine. An overlay slides in from the side of the screen to display the rule detail pane.
- On the rule detail pane click **Actions > Edit**.

Alternatively:

- Click the  icon on the row corresponding to the enricher you want to configure or modify.

- From the drop-down menu select **Edit**.

✓ Input fields marked with an asterisk are required.

- **Name**: define a name to identify the rule. It should be descriptive and easy to remember.
- **Description**: additional textual details. If you want, you can add a short description to provide more information and context.
- **Source**: from the drop-down menu select the incoming feed, enricher, or group whose entities and observables you want to augment with additional information.
- **Entity types**: from the drop-down menu select the entity types you want to enrich with additional information.
- **TLP**: from the drop-down menu select the TLP color code you want to use to filter enrichment data. **TLP** (<https://www.us-cert.gov/tlp>) provides an intuitive reference to assess how sensitive information is, focusing in particular on how serious it is, and whom it should or should not be shared with.
- Click **+ Add** or **+ More** to add a new filtering option. For example, to include another incoming feed or a different entity type.
- **Enrichers**: from the drop-down menu select one or more enrichers to apply the rule to. They are external data providers that are polled to obtain relevant enricher raw data; for example, whois lookup, reverse DNS, or GeoIP information.
- Select the **Enabled** checkbox to enable the rule immediately after creating it.
- Click **Save** to store your changes, or **Cancel** to discard them.

Delete enricher rules

To delete an enricher rule, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment**.
- The **Rules > Enrichment** page shows an overview of the configured enricher rules. You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.

To delete a specific rule, do the following:

- Click an area on the row corresponding to the rule you want to delete. An overlay slides in from the side of the screen to display the rule detail pane.
- On the rule detail pane click **Actions > Delete**.

Alternatively:

- Click the **⋮** icon on the row corresponding to the rule you want to delete.
- From the drop-down menu select **Delete**.
- On the confirmation pop-up dialog, click **Delete** to confirm the action.
- The rule is deleted.

Run the enricher

Automatically

To automatically enrich entities, make sure enricher tasks are active, and the necessary enrichment rules are configured.

Rules give you control over the type of information you want to retrieve or exclude, and what you want to do with it. You can assign one or more enricher sources to specific observable types. You can set multiple filters to cover usage scenarios as needed. You can then examine the returned enrichment observable data, as well as route it to other devices that enforce cyber threat detection or prevention.

To run the enricher automatically, go to the enricher edit mode, and make sure the **Enabled** checkbox on the edit form is selected.

If it is deselected, check it, and then click **Save**.

Manually

To adjust enrichment behavior to manually apply it to the entities you want to enrich, do the following:

- Open an entity in edit mode.
For example, on the top navigation bar click **Browse > Published** to display an overview of the published entities available in the platform.
- On the row corresponding to the entity you want to manually enrich, click the  icon to display the context menu.
- From the drop-down menu select **Edit**.
- At the bottom of the entity editor page click the **Manually enrich** checkbox.
A new input field with a drop-down menu becomes available.
- From the drop-down menu select one or more enrichers you want to apply to the entity.

Workflow

Add to dataset

Manually enrich

Enrichers to apply

Please select one or more options

- Select all options
- CVE Search enricher
- Censys Enricher
- Circl.lu IP's related to SSL Certificate
- Circl.lu SSL Certificate Fetcher

CANCEL SAVE DRAFT PUBLISH

- Click **Save draft** to store your changes without publishing the entity, **Publish** to release the new version of the entity including your changes, or **Cancel** to discard the changes.

Alternatively, you can manually enrich an entity by selecting it; for example, from a dataset, from **Browse** or from **Discovery**.

An overlay slides in from the side of the screen to display the entity detail pane.

- On the entity detail pane, click **Observables**.
- The **Observables** tab shows an overview of the enrichment observables the entity has been augmented with.

To manually enrich the entity observables:

- Click the  refresh icon to trigger a task run that polls all the enrichers configured for the entity.

Alternatively:

- From the **Actions** pop-up menu, select **Enrich > Enrich with all**.
- The platform polls all applicable enrichers for the entity, and it enriches all the entity observables with the retrieved data.

✕ Malicious files detected

Ingested: 06.10.2017 9:20 Incoming feed: TAXII Stand Samples TLP Not Set

OVERVIEW OBSERVABLES NEIGHBORHOOD JSON VERSIONS HISTORY

☰ | + ☰

<input type="checkbox"/>	Type ✓ Value	Relation	Sighted	Conn.	First seen	Maliciousness	🔄
<input type="checkbox"/>	hash-sha256: e3b0c44298fc1c149afb4c899...	Related +1		2	06.10.2017 9:20	●	⋮
<input type="checkbox"/>	hash-sha256: d7a8fbb307d7809469ca9abc...	Related +1		1	06.10.2017 9:20	●	⋮
<input type="checkbox"/>	file: readme.doc.exe	Related +1		1	06.10.2017 9:20	●	⋮

Edit

Delete

Add to dataset

Add to graph

Create task

Export >

Download original

Enrich >

Enrich with all (5)

Censys Enricher

CrowdStrike Enricher

FireEye

Flashpoint AggregINT Enricher

Flashpoint Thresher Enricher

To poll a specific enricher:

- From the **Actions** pop-up menu, select **Enrich**, and then click the specific enricher whose task run you want to trigger.
- The platform polls the specified enricher for the entity, and it enriches all supported entity observables with the retrieved data.

Malicious files detected

Ingested: 06.10.2017 9:20 Incoming feed: TAXII Stand Samples TLP Not Set

OVERVIEW OBSERVABLES NEIGHBORHOOD JSON VERSIONS HISTORY

3 selected Deselect all Enrich Add to

Type	Value	Relation	Sighted	Conn.	Business
<input checked="" type="checkbox"/>	hash-sha256: e3b0c44298fc1c149afb4c899...	Related +1		2	
<input checked="" type="checkbox"/>	hash-sha256: d7a8fbb307d7809469ca9abcb...	Related +1		1	
<input checked="" type="checkbox"/>	file: readme.doc.exe	Related +1		1	

Enrich with all (5)
Censys Enricher
CrowdStrike Enricher
FireEye
Flashpoint AggregINT Enricher
Flashpoint Thresher Enricher

To enrich only specific observables:

- On the **Observables** tab, select the checkboxes corresponding to the observables you want to enrich.
- From the **Enrich** drop-down menu, select **Enrich with all**.
- The platform polls all applicable enrichers for the entity, and it enriches the selected entity observables with the retrieved data.

Malicious files detected

Ingested: 06.10.2017 9:20 Incoming feed: TAXII Stand Samples TLP Not Set

OVERVIEW OBSERVABLES NEIGHBORHOOD JSON VERSIONS HISTORY

2 selected Deselect all Enrich Add to

Type	Value	Relation	Sighted	Conn.	Business
<input type="checkbox"/>	hash-sha256: e3b0c44298fc1c149afb4c899...	Related +1		2	
<input type="checkbox"/>	hash-sha256: d7a8fbb307d7809469ca9abcb...	Related +1		1	
<input checked="" type="checkbox"/>	file: readme.doc.exe	Related +1		1	

Enrich with all (5)
Censys Enricher
CrowdStrike Enricher
FireEye
Flashpoint AggregINT Enricher
Flashpoint Thresher Enricher

The available enricher tasks in the drop-down menu are automatically filtered to show only the applicable enrichers for the entity.

Enrichers automatically augment all the entities that accept the enricher's content type as an observable. In other words, the observable types an entity supports define the applicable enrichers an entity can use.

Review enrichment observables

RiskIQ PassiveTotal enrichers can take the following observable types as input:

- *domain, host, ipv4, ipv6*

RiskIQ PassiveTotal enrichers use these data types to look for additional information on observables. Any entity types supporting these observable types can be enriched with RiskIQ PassiveTotal enrichers.

To view enrichment information on the entity detail pane, do the following:

- Select an entity; for example, from a dataset, from **Browse** or from **Discovery**. An overlay slides in from the side of the screen to display the entity detail pane.
- On the entity detail pane, click **Observables**.
- The **Observables** tab shows an overview of the enrichment observables the entity has been augmented with.

Ingested: Yesterday at 23:59 Incoming feed: tor ○ TLP White

OVERVIEW **OBSERVABLES** NEIGHBORHOOD JSON VERSIONS HISTORY

Add observable

type / Value	Relation	Sighted	Conn.	First seen	Maliciousness
<input type="checkbox"/> domain: torstatus.blutmagie.de	Description + 1	96264	02.08.2017 14:52	●●●	⋮
<input type="checkbox"/> ipv4: 194.63.141.179	OpenResolve + 4		02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> email: registry@regfish.com	Threatcrowd AP...		02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-md5: e63989f8df535a14cee4a06484c...	Recorded Future		02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-sha256: c27c743c64713fd2a2b36b32...	Recorded Future		02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-sha512: 5a9df660747757935abfcdf4...	Recorded Future		02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> email: bitwisser@googlemail.com	Recorded Future		02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-sha1: 4e0c92f8e8dca4d9295c7587e7...	Recorded Future		02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-md5: b7532bac9c0d65b3a4a724a603...	Recorded Future		02.08.2017 14:53	●●●	⋮
<input type="checkbox"/> hash-sha256: 6ae3032f45266fd48589bfa8...	Recorded Future		02.08.2017 14:53	●●●	⋮

1 - 10 of 123 |< < > >|


Review enrichment observables on the graph

To view enrichment data and their connections with other entities and observables on the graph, do the following:


- On the row corresponding to the observable you want to load on the graph, click the  icon, and then select **Add to graph**.

Type	Value	Sightings	Maliciousness	Connections	Source	Timestamp	
ipV4	217.93.38.31			1	tor	29.08.2017 9:23	
domain	pd95d261f.dip0.t-ipconnect.de			1	tor		Ignore observable Create indicator Create sighting Add to graph Set maliciousness >
ipV4	93.238.180.183			1	Gecko Indicator...		
hash-md5	961b27607e5c2f7915558e1cee520bb4			7	Gecko CS indic...		
uri	https://www.threathq.com/p42/search/default?m=7413			1	Gecko Phishme...		

- To load the parent entity whose detail pane you are viewing, instead of its observables, from the pop-up **Actions** menu at the bottom of the pane select **Add to graph**.
- Click the graph thumbnail on the lower side of the screen to expand it.
- On the graph, right-click the entity you want to inspect, and from the context menu select **Load entities > All**, **Load observables > All** or **Load entities by extract > All**.




- Right-click an extract or an entity for further inspection and from the context menu select **Load entities > All**, **Load observables > All** or **Load entities by extract > All**.




To see how entities, observables and enrichment observables are connected, and to inspect relationships between distant items, do the following:

- **CTRL + click** two nodes on the graph to select them.
- Right-click either selected node, and from the context menu select **Find path** to query the graph database about the existence of a path between the nodes, or **Show path** to highlight an existing path on the graph.
- If a path does exist, the selected nodes and all the intermediate ones are highlighted on the graph to show the path that links them.



Search for enrichment observables

You can use the search box to look for enrichment observables. You can find the search box on the top bar:



Enter search terms and search queries, and then press **ENTER** or click the search icon to run the search. Searches you run through this search box are executed platform-wide.




The search functionality uses **Elasticsearch query syntax**

(<https://www.elastic.co/guide/en/elasticsearch/reference/current/full-text-queries.html>).


To access a cheatsheet with search examples using entity types, filters, and for help with the search syntax, click **Help** to display thematic drop-down lists with common search queries:

- **Filters:** examples of quick search filters.

- **Help:** examples of regex, Boolean, wildcards, and tag search usage.
- **Entities:** examples of searchable entity types.



Besides full text search, you can use Boolean operators, wildcards, regex, and you can combine these filtering options to create more refined searches.



Use operators to combine multiple quick filters and create a more complex search query.
Example:


```
enrichment_extracts.kind:domain AND enrichment_extracts.meta.classification:high
```

Field	Description	Example
<i>enrichment_extracts.id</i>	string — The alphanumeric ID string that uniquely identifies the enrichment observable.	01h12x45-01q2-1234-od01-123456h78h90
<i>enrichment_extracts.kind</i>	string — The enrichment observable data type.	domain
<i>enrichment_extracts.meta.blacklisted</i>	Boolean — An observable is blacklisted when it is included in the results returned by an <i>ignore</i> extraction rule. Allowed values: <code>true</code> , <code>false</code> .	true
<i>enrichment_extracts.meta.classification</i>	string — This value is defined in Rules by selecting appropriate options under Action and Confidence . Allowed classification metadata values are <code>good</code> , <code>bad</code> , and <code>unknown</code> .	good

Field	Description	Example
<code>enrichment_extracts.meta.confidence</code>	string — This value is defined in Rules by selecting the appropriate option under Action and Confidence . The selected action must be Mark as malicious for the Confidence drop-down list to become available. Allowed confidence metadata values are <code>low</code> , <code>medium</code> , and <code>high</code> .	<code>high</code>
<code>enrichment_extracts.value</code>	string — The actual value of the enrichment observable, based on the enrichment observable data type.	<code>doom.dismay.biz</code>

For reference, you can look up a complete list of all available search query fields in Kibana:

- To access Kibana, in the web browser address bar enter a URL with the following format:
`https://<platform_host>/api/kibana/app/kibana#/`
 Keep the trailing `/`
 Example: `https://platform.host.com/api/kibana/app/kibana#/`
- Select the **stix** index field:



- On the main menu bar, select **Settings**:

Discover
Visualize
Dashboard
Settings

Indices
Advanced
Objects
About

Index Patterns
+ Add New

- ★ logstash-*
- statsd-*
- stix

stix

★
↻
🗑️

This page lists every field in the stix index and the field's associated core type as recorded by Elasticsearch. While this list allows you to view the core type of each field, changing field types must be done using Elasticsearch's [Mapping API](#)

Fields (428)

Scripted fields (0)

name ↕	type ↕	format ↕	analyzed ⓘ ↕	indexed ⓘ ↕	controls
data.kill_chain_phases.kill_chain_name	string		✓	✓	
data.observable.object.related_objects.related_objects.relationship	string		✓	✓	
data.observable.composition.composition.composition.type	string		✓	✓	
data.producer.contributing_sources.type	string		✓	✓	
data.observable.object.related_objects.related_objects.properties_xml_type	string		✓	✓	
exposure.affected_overrides.state	boolean			✓	
data.test_mechanisms.rules.value	string		✓	✓	
data.indicated_ttps.idref	string		✓	✓	
data.handling.marking_structures.marking_structure_type	string		✓	✓	
exposure.sighted	boolean			✓	
exposure.prevent_ok	boolean			✓	
destinations	string			✓	
tags	string		✓	✓	

VirusTotal integration

Integrate EclecticIQ Platform with VirusTotal to retrieve malware information about DNSs, IPs, domains, and files.

VirusTotal	integration
Integration	VirusTotal
Type	enricher
API endpoint	<code>https://www.virustotal.com/vtapi/v2/{}</code>
Input	domain, hash-md5, hash-sha1, hash-sha256, ipv4, ipv6, uri
Output	Enriches supported observable types with maliciousness confidence level information.
Description	Polls data from the VirusTotal API. It provides information on malware, domains (passive DNS) and IP addresses. Submitted data is checked against 60+ antimalware products, resulting in a detection ratio output and additional metadata information, when available.

EclecticIQ Platform integrates with VirusTotal to use it as an intel source. The platform integrates with the VirusTotal API through an enricher.

To enable the VirusTotal integration you configure the VirusTotal enricher as needed, and then activate it or run it manually to poll the intel source.

Configure the enricher

Enrichment rules and enrichment tasks drive the enrichment process to:

- Poll selected and trustworthy intelligence data sources;
- Retrieve relevant, accurate, and reliable data to augment platform entities with additional bits of information that provide additional context.

Rules

Enrichment rules define what to do with the retrieved enrichment data.

Rules act like filters, and they set the logical constraints defining:

- The platform data sources to augment with enrichment information.
Data sources you can enrich are incoming feeds, other enrichers, and groups.
- Within the selected platform data sources, the entity type(s) to augment with enrichment information.
- The enrichers to use to fetch enrichment data.

Tasks

Enrichment tasks define process execution by setting the following options:

- The data fetching mechanism — for example, an API endpoint exposing the enrichment data service.
- Specific data sources — for example, datasets targeting threat actors like hackers and terrorist groups.

- Data rate limit and monthly execution cap values to control the amount of polled data.
- A source reliability flag for the incoming enrichment data to simplify assessing the quality of the retrieved data.

Observables

Observables augment the entities they are related to by providing additional context that can help discover indirect relationships or spawn new relationships between entities.

Observables are atomic and factual: an observable represents one discrete piece of information that describes a fact. For example, an IP address, a hash value, the name of a location or an actor.

Configure enricher tasks

To configure or to edit an enricher task, do the following:

- On the top navigation bar click **Data configuration > Enrichers**.
- On the enricher overview page click the tile corresponding to the enricher you want to configure or modify.
- On the enricher detail page click the **Edit** button.

✔ Input fields marked with an asterisk are required.

- **Observable types:** select one or more observable types you want to enrich with data retrieved through the VirusTotal enricher.

Supported observable types:

- *domain*
- *hash-md5*
- *hash-sha1*
- *hash-sha256*
- *ipv4*
- *ipv6*
- *uri*

Under **Parameters**, define the specific configuration options for the VirusTotal enricher:

- **API key: sign up** (<https://www.virustotal.com/en/documentation/public-api/#getting-started>) to the VirusTotal community to automatically be assigned a personal API key to access the VirusTotal public API, and then enter it in this field.
- **Scan URLs:** select this checkbox to to **submit URLs** (<https://www.virustotal.com/en/documentation/public-api/#scanning-urls>) to VirusTotal.
- **Scan files:** select this checkbox to to **submit files/file hashes** (<https://www.virustotal.com/en/documentation/public-api/#scanning-files>) to VirusTotal. File hashes are embedded inside entities as raw artifacts.

- **Max low confidence infection rate**: you can set an *upper threshold* to automatically flag enriched observables with a *low confidence* value.
After completing the sample analysis, enriched observables with a *lower* detection ratio than the specified value are flagged as **Malicious - Low confidence**.
 - Enter a numeric value between *0.1* and *0.9* — that is, $0 < value < 1$.
 - Default value: *0.3*.
- **Min high confidence infection rate**: you can set a *bottom threshold* to automatically flag enriched observables with a *high confidence* value.
After completing the sample analysis, enriched observables with a *higher* detection ratio than the specified value are flagged as **Malicious - High confidence**.
 - Enter a numeric value between *0.1* and *0.9* — that is, $0 < value < 1$.
 - Default value: *0.6*.
- Enriched observables with a detection ratio falling in the range defined by **Max low confidence infection rate** (range lower limit) and **Min high confidence infection rate** (range upper limit) are flagged as **Malicious - Medium confidence**.
- Click **Save** to store your changes, or **Cancel** to discard them.

Configure enricher rules

Add enricher rules

To add a new enricher rule, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment**.
- The **Rules > Enrichment** page shows an overview of the configured enricher rules.
You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.
- Click the + icon.

✓ Input fields marked with an asterisk are required.

On the **Create enrichment rule** page, fill out the fields to create the new enricher rule:

- **Name**: define a name to identify the rule. It should be descriptive and easy to remember.
- **Description**: additional textual details. If you want, you can add a short description to provide more information and context.
- Click **+ Add** or **+ More** to add a filtering option.
- **Source**: from the drop-down menu select the incoming feed, enricher, or group whose entities and observables you want to augment with additional information.

- **Entity types:** from the drop-down menu select the entity types you want to enrich with additional information.
- **TLP:** from the drop-down menu select the TLP color code you want to use to filter enrichment data.
TLP (<https://www.us-cert.gov/tlp>) provides an intuitive reference to assess how sensitive information is, focusing in particular on how serious it is, and whom it should or should not be shared with.
- Click **+ Add** or **+ More** to add a new filtering option. For example, to include another incoming feed or a different entity type. A filter can take only one source and one entity type at a time, but you can set up rules with as many filters as you need.
- **Enrichers:** from the drop-down menu select one or more enrichers to apply the rule to.
When a rule is applied to one or more enrichers, it filters the enrichment data polled from the enricher source, based on the specified rule filters and criteria.
- Select the **Enabled** checkbox to enable the rule immediately after creating it.
- Click **Save** to store your changes, or **Cancel** to discard them.

Save options

Besides committing current data by clicking **Save**, you can also click the downward-pointing arrow on the **Save** button to display a context menu with additional save options:

- **Save and new:** saves the current data for the active item, and it allows you to start creating a new item of the same type right away. For example, a dataset, a feed, a rule, a workspace, or a task.
- **Save and duplicate:** saves the current data for the active item, and it creates a pre-populated copy of the same item, which you can use as a template to speed up manual creation work.

Edit enricher rules

To edit enricher rules, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment**.
- The **Rules > Enrichment** page shows an overview of the configured enricher rules.
You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.

To edit the details of a specific rule, do the following:

- Click an area on the row corresponding to the rule you want to examine. An overlay slides in from the side of the screen to display the rule detail pane.
- On the rule detail pane click **Actions > Edit**.

Alternatively:

- Click the  icon on the row corresponding to the enricher you want to configure or modify.
- From the drop-down menu select **Edit**.

 Input fields marked with an asterisk are required.

- **Name:** define a name to identify the rule. It should be descriptive and easy to remember.

- **Description:** additional textual details. If you want, you can add a short description to provide more information and context.
- **Source:** from the drop-down menu select the incoming feed, enricher, or group whose entities and observables you want to augment with additional information.
- **Entity types:** from the drop-down menu select the entity types you want to enrich with additional information.
- **TLP:** from the drop-down menu select the TLP color code you want to use to filter enrichment data.
TLP (<https://www.us-cert.gov/tlp>) provides an intuitive reference to assess how sensitive information is, focusing in particular on how serious it is, and whom it should or should not be shared with.
- Click **+ Add** or **+ More** to add a new filtering option. For example, to include another incoming feed or a different entity type.
- **Enrichers:** from the drop-down menu select one or more enrichers to apply the rule to. They are external data providers that are polled to obtain relevant enricher raw data; for example, whois lookup, reverse DNS, or GeoIP information.
- Select the **Enabled** checkbox to enable the rule immediately after creating it.
- Click **Save** to store your changes, or **Cancel** to discard them.

Delete enricher rules

To delete an enricher rule, do the following:

- On the top navigation bar click **Data configuration > Rules > Enrichment**.
- The **Rules > Enrichment** page shows an overview of the configured enricher rules.
You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.

To delete a specific rule, do the following:

- Click an area on the row corresponding to the rule you want to delete. An overlay slides in from the side of the screen to display the rule detail pane.
- On the rule detail pane click **Actions > Delete**.

Alternatively:

- Click the  icon on the row corresponding to the rule you want to delete.
- From the drop-down menu select **Delete**.
- On the confirmation pop-up dialog, click **Delete** to confirm the action.
- The rule is deleted.

Run the enricher

Automatically

To automatically enrich entities, make sure enricher tasks are active, and the necessary enrichment rules are configured.

Rules give you control over the type of information you want to retrieve or exclude, and what you want to do with it. You can assign one or more enricher sources to specific observable types. You can set multiple filters to cover usage scenarios as needed. You can then examine the returned enrichment observable data, as well as route it to other devices that enforce cyber threat detection or prevention.

To run the enricher automatically, go to the enricher edit mode, and make sure the **Enabled** checkbox on the edit form is selected.

If it is deselected, check it, and then click **Save**.

Manually

To adjust enrichment behavior to manually apply it to the entities you want to enrich, do the following:

- Open an entity in edit mode.
For example, on the top navigation bar click **Browse > Published** to display an overview of the published entities available in the platform.
- On the row corresponding to the entity you want to manually enrich, click the **⋮** icon to display the context menu.
- From the drop-down menu select **Edit**.
- At the bottom of the entity editor page click the **Manually enrich** checkbox.
A new input field with a drop-down menu becomes available.
- From the drop-down menu select one or more enrichers you want to apply to the entity.

Workflow

Add to dataset

Manually enrich

Enrichers to apply

Please select one or more options

- Select all options
- CVE Search enricher
- Censys Enricher
- Circl.lu IP's related to SSL Certificate
- Circl.lu SSL Certificate Fetcher

CANCEL SAVE DRAFT PUBLISH

- Click **Save draft** to store your changes without publishing the entity, **Publish** to release the new version of the entity including your changes, or **Cancel** to discard the changes.

Alternatively, you can manually enrich an entity by selecting it; for example, from a dataset, from **Browse** or from **Discovery**.

An overlay slides in from the side of the screen to display the entity detail pane.


- On the entity detail pane, click **Observables**.
- The **Observables** tab shows an overview of the enrichment observables the entity has been augmented with.

To manually enrich the entity observables:

- Click the  refresh icon to trigger a task run that polls all the enrichers configured for the entity.

Alternatively:

- From the **Actions** pop-up menu, select **Enrich > Enrich with all**.
- The platform polls all applicable enrichers for the entity, and it enriches all the entity observables with the retrieved data.



The screenshot shows the 'Malicious files detected' entity detail pane. The top header is teal with a close button and the title. Below the header, there's a status bar showing 'Ingested: 06.10.2017 9:20' and 'Incoming feed: TAXII Stand Samples'. A 'TLP Not Set' button is on the right. The main content area has tabs for OVERVIEW, OBSERVABLES, NEIGHBORHOOD, JSON, VERSIONS, and HISTORY. The OBSERVABLES tab is active, showing a table of observables. Below the table, an 'Actions' menu is open, highlighting the 'Enrich' option, which has opened a sub-menu with 'Enrich with all (5)' and several enrichers: Censys Enricher, CrowdStrike Enricher, FireEye, Flashpoint AggregINT Enricher, and Flashpoint Thresher Enricher.

Type	Value	Relation	Sighted	Conn.	First seen	Maliciousness
hash-sha256	e3b0c44298fc1c149afb4c899...	Related +1		2	06.10.2017 9:20	
hash-sha256	d7a8fbb307d7809469ca9abcb...	Related +1		1	06.10.2017 9:20	
file	readme.doc.exe	Related +1		1	06.10.2017 9:20	

To poll a specific enricher:

- From the **Actions** pop-up menu, select **Enrich**, and then click the specific enricher whose task run you want to trigger.
- The platform polls the specified enricher for the entity, and it enriches all supported entity observables with the retrieved data.

Malicious files detected

Ingested: 06.10.2017 9:20 Incoming feed: TAXII Stand Samples TLP Not Set

OVERVIEW OBSERVABLES NEIGHBORHOOD JSON VERSIONS HISTORY

3 selected Deselect all Enrich Add to

Type	Value	Relation	Sighted	Conn.	Business
<input checked="" type="checkbox"/>	hash-sha256: e3b0c44298fc1c149afb4c899...	Related +1		2	
<input checked="" type="checkbox"/>	hash-sha256: d7a8fbb307d7809469ca9abcb...	Related +1		1	
<input checked="" type="checkbox"/>	file: readme.doc.exe	Related +1		1	

Enrich with all (5)
Censys Enricher
CrowdStrike Enricher
FireEye
Flashpoint AggregINT Enricher
Flashpoint Thresher Enricher

To enrich only specific observables:

- On the **Observables** tab, select the checkboxes corresponding to the observables you want to enrich.
- From the **Enrich** drop-down menu, select **Enrich with all**.
- The platform polls all applicable enrichers for the entity, and it enriches the selected entity observables with the retrieved data.

Malicious files detected

Ingested: 06.10.2017 9:20 Incoming feed: TAXII Stand Samples TLP Not Set

OVERVIEW OBSERVABLES NEIGHBORHOOD JSON VERSIONS HISTORY

2 selected Deselect all Enrich Add to

Type	Value	Relation	Sighted	Conn.	Business
<input type="checkbox"/>	hash-sha256: e3b0c44298fc1c149afb4c899...	Related +1		2	
<input type="checkbox"/>	hash-sha256: d7a8fbb307d7809469ca9abcb...	Related +1		1	
<input checked="" type="checkbox"/>	file: readme.doc.exe	Related +1		1	

Enrich with all (5)
Censys Enricher
CrowdStrike Enricher
FireEye
Flashpoint AggregINT Enricher
Flashpoint Thresher Enricher

The available enricher tasks in the drop-down menu are automatically filtered to show only the applicable enrichers for the entity.

Enrichers automatically augment all the entities that accept the enricher's content type as an observable. In other words, the observable types an entity supports define the applicable enrichers an entity can use.

Review enrichment observables

The VirusTotal enricher can take the following observable types as input:

- *domain, hash-md5, hash-sha1, hash-sha256, ipv4, ipv6, uri*

The enricher uses these input data types to look for additional information to enrich existing observables with. Any entity types supporting these observable types can be enriched with VirusTotal.

To view enrichment information on the entity detail pane, do the following:

- Select an entity; for example, from a dataset, from **Browse** or from **Discovery**. An overlay slides in from the side of the screen to display the entity detail pane.
- On the entity detail pane, click **Observables**.
- The **Observables** tab shows an overview of the enrichment observables the entity has been augmented with.

Ingested: Yesterday at 23:59 Incoming feed: tor ○ TLP White

OVERVIEW **OBSERVABLES** NEIGHBORHOOD JSON VERSIONS HISTORY

Add observable

type / Value	Relation	Sighted	Conn.	First seen	Maliciousness	
<input type="checkbox"/> domain: torstatus.blutmagie.de	Description + 1	96264	02.08.2017 14:52	14:52	●●●	⋮
<input type="checkbox"/> ipv4: 194.63.141.179	OpenResolve + 4		02.08.2017 14:53	14:53	●●●	⋮
<input type="checkbox"/> email: registry@regfish.com	Threatcrowd AP...		02.08.2017 14:53	14:53	●●●	⋮
<input type="checkbox"/> hash-md5: e63989f8df535a14cee4a06484c...	Recorded Future		02.08.2017 14:53	14:53	●●●	⋮
<input type="checkbox"/> hash-sha256: c27c743c64713fd2a2b36b32...	Recorded Future		02.08.2017 14:53	14:53	●●●	⋮
<input type="checkbox"/> hash-sha512: 5a9df660747757935abfcdf4...	Recorded Future		02.08.2017 14:53	14:53	●●●	⋮
<input type="checkbox"/> email: bitwisser@googlemail.com	Recorded Future		02.08.2017 14:53	14:53	●●●	⋮
<input type="checkbox"/> hash-sha1: 4e0c92f8e8dca4d9295c7587e7...	Recorded Future		02.08.2017 14:53	14:53	●●●	⋮
<input type="checkbox"/> hash-md5: b7532bac9c0d65b3a4a724a603...	Recorded Future		02.08.2017 14:53	14:53	●●●	⋮
<input type="checkbox"/> hash-sha256: 6ae3032f45266fd48589bfa8...	Recorded Future		02.08.2017 14:53	14:53	●●●	⋮

1 - 10 of 123 |< < > >|


Review enrichment observables on the graph

To view enrichment data and their connections with other entities and observables on the graph, do the following:


- On the row corresponding to the observable you want to load on the graph, click the  icon, and then select **Add to graph**.

Type	Value	Sightings	Maliciousness	Connections	Source	Timestamp	
ipV4	217.93.38.31	1	●	1	tor	29.08.2017 9:23	
domain	pd95d261f.dip0.t-ipconnect.de	1	●●●	1	tor		Ignore observable Create indicator Create sighting Add to graph Set maliciousness >
ipV4	93.238.180.183	1	●	1	Gecko Indicator...		
hash-md5	961b27607e5c2f7915558e1cee520bb4	7	●●●●●	7	Gecko CS indic...		
uri	https://www.threathq.com/p42/search/default?m=7413	1	●	1	Gecko Phishme...		

- To load the parent entity whose detail pane you are viewing, instead of its observables, from the pop-up **Actions** menu at the bottom of the pane select **Add to graph**.
- Click the graph thumbnail on the lower side of the screen to expand it.
- On the graph, right-click the entity you want to inspect, and from the context menu select **Load entities > All**, **Load observables > All** or **Load entities by extract > All**.




- Right-click an extract or an entity for further inspection and from the context menu select **Load entities > All**, **Load observables > All** or **Load entities by extract > All**.




To see how entities, observables and enrichment observables are connected, and to inspect relationships between distant items, do the following:

- **CTRL + click** two nodes on the graph to select them.
- Right-click either selected node, and from the context menu select **Find path** to query the graph database about the existence of a path between the nodes, or **Show path** to highlight an existing path on the graph.
- If a path does exist, the selected nodes and all the intermediate ones are highlighted on the graph to show the path that links them.



Search for enrichment observables

You can use the search box to look for enrichment observables. You can find the search box on the top bar:



Enter search terms and search queries, and then press **ENTER** or click the search icon to run the search. Searches you run through this search box are executed platform-wide.




The search functionality uses **Elasticsearch query syntax**

(<https://www.elastic.co/guide/en/elasticsearch/reference/current/full-text-queries.html>).


To access a cheatsheet with search examples using entity types, filters, and for help with the search syntax, click **Help** to display thematic drop-down lists with common search queries:

- **Filters:** examples of quick search filters.

- **Help:** examples of regex, Boolean, wildcards, and tag search usage.
- **Entities:** examples of searchable entity types.



Besides full text search, you can use Boolean operators, wildcards, regex, and you can combine these filtering options to create more refined searches.



Use operators to combine multiple quick filters and create a more complex search query.
Example:


```
enrichment_extracts.kind:domain AND enrichment_extracts.meta.classification:high
```

Field	Description	Example
<i>enrichment_extracts.id</i>	string — The alphanumeric ID string that uniquely identifies the enrichment observable.	01h12x45-01q2-1234-od01-123456h78h90
<i>enrichment_extracts.kind</i>	string — The enrichment observable data type.	domain
<i>enrichment_extracts.meta.blacklisted</i>	Boolean — An observable is blacklisted when it is included in the results returned by an <i>ignore</i> extraction rule. Allowed values: <code>true</code> , <code>false</code> .	true
<i>enrichment_extracts.meta.classification</i>	string — This value is defined in Rules by selecting appropriate options under Action and Confidence . Allowed classification metadata values are <code>good</code> , <code>bad</code> , and <code>unknown</code> .	good

Field	Description	Example
<code>enrichment_extracts.meta.confidence</code>	string — This value is defined in Rules by selecting the appropriate option under Action and Confidence . The selected action must be Mark as malicious for the Confidence drop-down list to become available. Allowed confidence metadata values are <code>low</code> , <code>medium</code> , and <code>high</code> .	<code>high</code>
<code>enrichment_extracts.value</code>	string — The actual value of the enrichment observable, based on the enrichment observable data type.	<code>doom.dismay.biz</code>

For reference, you can look up a complete list of all available search query fields in Kibana:

- To access Kibana, in the web browser address bar enter a URL with the following format:
`https://<platform_host>/api/kibana/app/kibana#/`
 Keep the trailing `/`
 Example: `https://platform.host.com/api/kibana/app/kibana#/`
- Select the **stix** index field:



- On the main menu bar, select **Settings**:

Discover
Visualize
Dashboard
Settings

Indices
Advanced
Objects
About

Index Patterns
+ Add New

- ★ logstash-*
- statsd-*
- stix

stix

★
↻
🗑️

This page lists every field in the stix index and the field's associated core type as recorded by Elasticsearch. While this list allows you to view the core type of each field, changing field types must be done using Elasticsearch's [Mapping API](#)

Fields (428)

Scripted fields (0)

name ↕	type ↕	format ↕	analyzed ⓘ ↕	indexed ⓘ ↕	controls
data.kill_chain_phases.kill_chain_name	string		✓	✓	✎
data.observable.object.related_objects.related_objects.relationship	string		✓	✓	✎
data.observable.composition.composition.composition.type	string		✓	✓	✎
data.producer.contributing_sources.type	string		✓	✓	✎
data.observable.object.related_objects.related_objects.properties_xml_type	string		✓	✓	✎
exposure.affected_overrides.state	boolean			✓	✎
data.test_mechanisms.rules.value	string		✓	✓	✎
data.indicated_ttps.idref	string		✓	✓	✎
data.handling.marking_structures.marking_structure_type	string		✓	✓	✎
exposure.sighted	boolean			✓	✎
exposure.prevent_ok	boolean			✓	✎
destinations	string			✓	✎
tags	string		✓	✓	✎

Splunk integration

EclecticIQ Platform App for Splunk Enterprise enables Splunk users to ingest large quantities of threat intelligence by integrating EclecticIQ Platform feeds with Splunk Enterprise.

Splunk	integration
App	EclecticIQ Platform App for Splunk
Version	1.0.2
Compatibility	Splunk Enterprise 6.3 and later
Last changed	July 2017
Authors	SOC Prime, EclecticIQ
Type	SIEM integration
Integration	app/bidirectional
Description	The app integrates EclecticIQ Platform feeds with Splunk Enterprise. Outgoing feeds transmit relevant data to Splunk for analysis and further filtering to identify potential threats that may target your organization.
Download	Splunkbase (https://splunkbase.splunk.com/app/3408/)

Release notes

Version 1.0.2 — Several known issues were addressed.

Contact

If you want to send us your feedback or if you need any support with the app, you can contact EclecticIQ at splunk@eclecticiq.com.

To request further documentation, contact EclecticIQ at splunk@eclecticiq.com.

To suggest a feature request and to report bugs, send an email to splunk@eclecticiq.com.


About EclecticIQ Platform App for Splunk

EclecticIQ Platform App for Splunk is an app for Splunk Enterprise. It enables Splunk users to ingest large quantities of threat intelligence by integrating EclecticIQ Platform feeds with Splunk.

EclecticIQ Platform ingests cyber threat data in different formats from multiple sources. The platform deduplicates, normalizes, and enriches source data with additional contextual details, and then it uses outgoing feeds to output relevant information to Splunk, where it can be analyzed and filtered by a set of rules to identify matching threats that may target your organization.

This process generates sightings and alerts that Splunk feeds back to EclecticIQ Platform, providing a rich threat intelligence dataset that allows you to efficiently tune your SIEM prevention and detection system.

EclecticIQ Platform App for Splunk ships with a default set of dashboard gauges to make it easier for Splunk users to monitor feed data collection, as well as to analyze and triage any *indicators of compromise* (IOCs) the data analysis process may yield.



Quick start guide

Compatibility

Splunk Enterprise 6.3 and later — EclecticIQ Platform App for Splunk 1.0.2

- EclecticIQ Platform App for Splunk 1.0.2
- Supports Splunk Enterprise 6.3 and later.
- Supports Python 2.6.6 or higher 2.x.x version.
Not supported: Python 3.x.x.
- Required Python libraries: **argparse** (<https://pypi.python.org/pypi/argparse>), **requests** (<https://pypi.python.org/pypi/requests>).

Install

EclecticIQ Platform App for Splunk is developed specifically for Splunk Enterprise.

Everything you need to use the app is bundled with the installation package and the related files.

If you are using Splunk Enterprise, you do not need to install the script and configuration files.

- Verify that the Splunk Enterprise server you want to install EclecticIQ Platform App for Splunk on is compatible with the app.
- Verify that the required necessary Python libraries are installed.

- In the Splunk management console go to **Apps > Manage Apps**, and then click **Install app from file**.
- Browse to the location where the *eclecticiq-platform-app-for-splunk-<version_number>.tgz* file is stored, and then click **Upload**.
- After successfully completing the upload and the installation, restart Splunk.

Configure

After restarting Splunk, you can proceed to configuring EclecticIQ Platform App for Splunk.

- In the Splunk management console go to **Apps**.
- From the app list select **EclecticIQ Platform App for Splunk**.
- On the displayed dialog window click **Continue to app setup page**.

On the EclecticIQ Platform App for Splunk configuration screen, define the following options:

- **Feeds setup**: enter the feed ID of the EclecticIQ Platform outgoing feeds whose content you want to send to Splunk. If you enter multiple feed IDs use a comma (,) as a separator.
- **Input setup**: define the indexes and the source types you are using as data sources for this integration:
 - **Indexes**: enter the name of the **Splunk indexes** (<http://docs.splunk.com/splexicon:index>) you want to include as sources. If you enter multiple indexes, use a comma (,) as a separator.
 - **Sourcetypes**: enter the name of the **Splunk source types** (<https://docs.splunk.com/splexicon:sourcetype>) you want to include. If you enter multiple source type names, use a comma (,) as a separator.
- **Select the type of Sighting to send to EclecticIQ Platform**: select all applicable checkboxes corresponding to the data types you want to use to generate the sightings that are subsequently sent for ingestion to EclecticIQ Platform.
- **EclecticIQ platform URL**: enter the URL corresponding to the address of the EclecticIQ Platform host.
- **Verify SSL Connection**: select this checkbox to enable SSL verification for the connection, if applicable.
- **EclecticIQ source group name**: enter the name of the group you want to use as a source.
- **EclecticIQ platform authentication**: enter a valid user name and a password to authenticate and to sign in to the platform.
- Click **Save** to save and store your configuration.
- By default, a script is configured to run and collect outgoing feeds once every 2 hours at *hour:00 mins*; that is, at 00:00, 02:00, 04:00, and so on.
- By default, a script is configured to push sightings once a day at 01:00 AM.
- You can change the job schedules in the following configuration file: `$SPLUNK_HOME/etc/apps/eclecticiq-platform-app-for-splunk/default/inputs.conf`
 - *eiq_collect_feeds.py* is the script that collects outgoing feed data from EclecticIQ Platform.
 - *eiq_send_sightings.py* is the script that sends sightings to EclecticIQ Platform.

After correctly configuring EclecticIQ Platform App for Splunk to integrate and work with Splunk, the corresponding dashboard view should become populated with relevant results.

Uninstall

To uninstall EclecticIQ Platform App for Splunk, run the following command(s):

```
$ SPLUNK_HOME/bin/splunk remove app eclecticiq-platform-app-for-splunk
```

Install and configure Python

To check which Python version is installed on the target server, run the following command(s):

```
$ python -V
```

- If you need to install the required Python version, **download it** (<https://www.python.org/downloads/source/>), and then follow the **installation instructions** (<https://docs.python.org/2/using/unix.html>).
- If the required Python version is installed, check if *pip* is available on the server:

```
$ pip -V
```

- If you need to install pip, **download get-pip.py** (<https://bootstrap.pypa.io/get-pip.py>), and then follow the **installation instructions** (<https://pip.pypa.io/en/latest/installing.html>):

```
# get pip
$ wget https://bootstrap.pypa.io/get-pip.py

# install pip
$ python get-pip.py
```

- Use pip to check that the necessary libraries are available:

```
$ pip list
```

- If the *argparse* and the *requests* libraries are missing, install them:

```
$ pip install argparse
$ pip install requests
```

End of the EclecticIQ Platform App for Splunk quick start guide

Beginning of the EclecticIQ Platform App for Splunk integration guide

EclecticIQ Platform integration with Splunk

(Through EclecticIQ Platform App for Splunk)

Before you start

Before you start installing the app, take a moment to review the preliminary requirements and the main steps of the process.


Requirements


- An EclecticIQ Platform installation.
- A Splunk server installation.
- Install and set up EclecticIQ Platform App for Splunk on a Splunk server that has network access to the EclecticIQ Platform server: these servers need to communicate and exchange data.
- Supports Splunk Enterprise 6.3 and later.
- Supports Python 2.6.6 or higher 2.x.x version.
Not supported: Python 3.x.x.
- Required Python libraries: **argparse** (<https://pypi.python.org/pypi/argparse>), **requests** (<https://pypi.python.org/pypi/requests>).

Process outline

The diagram sums up the main steps to set up and configure a platform integration with Splunk:

- First, you set up the outgoing feed sending data from the platform to Splunk.
- Then, you install and configure EclecticIQ Platform App for Splunk to enable the integration between the platform and Splunk.





Configure EclecticIQ CSV outgoing feeds

EclecticIQ Platform enables you to configure outgoing feeds to share and distribute cyber threat intelligence in several formats. Share knowledge and promote collaboration to support an ecosystem where partners work together to identify threats, and define an effective course of action to ensure their assets are protected.

This section describes how to configure **EclecticIQ Entities CSV** and **EclecticIQ Observables CSV** outgoing feeds, so that you can distribute selected intelligence through EclecticIQ Platform.

Configure the general options

✓ Input fields marked with an asterisk are required.

- On the top navigation bar, select **Data configuration > Outgoing feeds**.
- On the top-left corner of the page click the **+** icon to open the outgoing feed editor.

The **Outgoing feeds** page displays an overview of the configured outgoing feeds to publish and distribute selected intelligence from the platform to external parties, services, and systems.

On the **Create outgoing feed** form you can populate the input fields to define the intel provider/data source for the feed, and the feed behavior.

- Under **Feed name**, enter a name for the feed you are creating. It should be descriptive and easy to remember.

Transport and content

Under **Transport type** and **Content type**, select the appropriate options to configure transport and content for the specified outgoing feed.

- **Transport type**: from the drop-down menu select the appropriate transport type to publish data through the outgoing feed.
You can implement this integration through the **HTTP download** and **Mount point upload** transport types.
- **Content type**: from the drop-down menu select **EclecticIQ Entities CSV** or **EclecticIQ Observables CSV** and configure the appropriate parameters under **Content configuration**, when applicable.
- **Dataset**: from the drop-down menu select one or more datasets as data sources for the outgoing feed.
- **Update strategy**: from the drop-down menu select the preferred method to update the data:
 - **Append**: every time the outgoing feed task runs, only new data from the latest task run, that is, only new entities, is appended to the existing data.
When the outgoing feed task runs, it includes only new entities.
 - **Replace** every time the outgoing feed task runs, it publishes only new data.
When the outgoing feed task runs, it produces new content that can include new, as well as existing entities.
 - **Diff**: every time the outgoing feed task runs, new data is compared against existing data to identify any differences between the two datasets at observable-level — any observable added to or removed from the entities in the set — or at entity-level — any entities added to or removed from the set.
Depending on the selected CSV content option, each row in the CSV output contains information about one entity or one observable.
An extra diff column is added to the output to indicate if a row, and therefore either an entity or an observable, was added to or removed from the set.
This option allows you to identify any changes in a feed between two task runs without downloading the whole feed.

Set a schedule

Under **Execution schedule** you can define how often you want to run the feed task:

- **None**: scheduled feed execution is disabled. You need to manually trigger the task to ingest or to publish data through an incoming or an outgoing feed, respectively.
- **Every [n] minutes**: the feed task runs automatically once every [n] minutes, where [n] defines the selected time interval in minutes.
You define the execution interval in 5-minute increments from the corresponding drop-down menu.

- **Every hour, [n] minutes past the hour**: the feed task runs automatically once an hour every hour at the specified minute offset from the hour.
You define how long in minutes after the beginning of an hour the task should run from the corresponding drop-down menu.
- **Every [n] hours**: the feed task runs automatically once every [n] hours, where [n] defines the time interval in hours between two consecutive feed task runs.
You define how long the time interval between feed executions should be by selecting the number of hours from the corresponding drop-down menu.
- **Every day at [time]**: the feed task runs automatically once a day at the specified time.
You define the time of the day when the task should run from the corresponding drop-down menus.
- **Every [n] days**: the feed task runs automatically once every [n] days, where [n] defines the time interval in days between two consecutive feed task runs.
You define how long the time interval between feed executions should be by selecting the number of days from the corresponding drop-down menu.
- **Every week on [day of the week] at [time]**: the feed task runs automatically once a week on the designated day, at the specified time.
You define the day of the week and time of the day when the task should run from the corresponding drop-down menus.
- **Every month on [day of the month] at [time]**: the feed task runs automatically once a month on the designated day of the month, at the specified time.
You define the day of the week and time of the day when the task should run from the corresponding drop-down menus.
Keep in mind that not all months of the year have 30 or 31 days.

Set a TLP override

- **Override TLP** overwrites the **TLP** (<https://www.us-cert.gov/tlp>) color code associated with the feed entities with the one you set here. The selected TLP value is assigned to all the entities in the feed.

You can override the original or the current TLP color code of an entity, an incoming feed, or an outgoing feed.

When working as a filter, TLP colors select a decreasing range: if you set a TLP color as a filter the enricher, the feed, or the returned filtered results include all the entities flagged with the selected TLP color code, as well as all the entities whose TLP color indicates that they are progressively lower risk, less sensitive, and suitable for disclosure to broader audiences.

For example, if you select green the filtered results include entities with a TLP color set to green, as well as entities with a TLP color set to white, and entities with no TLP color code flag.

- The **Filter TLP color** options allow including in the feed data only an entity subset, based on the selected **TLP** (<https://www.us-cert.gov/tlp>) value.
If you set a TLP color as a filter, the feed includes all the entities flagged with the selected TLP color code, as well as the entities whose TLP color indicates that they are suitable for progressively broader audiences. For example, if you select green, the feed includes entities with a TLP color set to green and entities with a TLP color set to white.

Set reliability and relevancy

- **Source reliability:** from the drop-down menu select an option to flag the feed or enricher content with a predefined reliability value to help other users assess how trustworthy the data source is.
Values in this menu have the same meaning as the first character in the **two-character Admiralty System code** (https://en.wikipedia.org/wiki/admiralty_code).
Example: *B - Usually reliable*
- **Relevancy threshold (%)** allows you to set a filter to include in the feed only entities whose relevancy is higher than the value defined here.

Set observable filters

- **Allowed observable states:** from the drop-down menu select one or more observable states to include in the feed data only entities whose observable states match at least one of the selections defined here.
- **Observable types:** from the drop-down menu select one or more observable types to include in the outgoing feed only entities whose observable types match at least one of the selections defined here.
- **Enrichment observable types:** from the drop-down menu select one or more enrichment observable types to include in the outgoing feed only entities whose enrichment observable types match at least one of the selections defined here.
- Click **Save** to store your changes, or **Cancel** to discard them.

The filters work independently of each other: there are no Boolean **AND** or **OR** to join multiple filters into a serial pipeline.

Save options

Besides committing current data by clicking **Save**, you can also click the downward-pointing arrow on the **Save** button to display a context menu with additional save options:

- **Save and new:** saves the current data for the active item, and it allows you to start creating a new item of the same type right away. For example, a dataset, a feed, a rule, a workspace, or a task.
- **Save and duplicate:** saves the current data for the active item, and it creates a pre-populated copy of the same item, which you can use as a template to speed up manual creation work.

Configure the transport type

Transport types	Allowed content types
HTTP download	EclectiQ Entities CSV
	EclectiQ Observables CSV
Mount point upload	EclectiQ Entities CSV
	EclectiQ Observables CSV

HTTP download



The HTTP download transport type requires basic access authentication.

If you want to make the outgoing feed data available through an HTTP URL, from the **Transport type** drop-down list select **HTTP download**.

Under **Transport configuration**, configure the following settings:

- **Public:** default setting: deselected.
Select this checkbox to make the outgoing feed available to all platform groups and to all platform users. Leave it deselected to make the outgoing feed available only to specific groups. You can select the intended recipient groups in the **Authorized groups** drop-down menu.
- **Authorized groups:** restricts access to the outgoing feed to the groups you select from the drop-down menu, and to their member users.
The **Authorized groups** option is available only when the **Public** checkbox is deselected (default setting).

Mount point upload

If the source of the feed is located on a local or network unit, from the **Transport type** drop-down list select the **Mount point upload** option.

After selecting **Transport type > Mount point upload**, set the origin location for the source data:

- **Mount point path:** enter the path to the local or network unit where the source data for the outgoing feed is stored.

Configure the content type

When you set up an outgoing feed from the platform to the destination Splunk instance, you need to configure the following content type parameters.

From the drop-down menu select one of the following options to define the preferred structure for the output data and the resulting layout in the CSV output:

- **EclecticIQ Entities CSV:** in the resulting CSV with column headers, each row holds information referring to one entity. For example, an indicator, a TTP, and so on.
- **EclecticIQ Observables CSV:** in the resulting CSV with column headers, each row holds information referring to one observable. For example, an IP address, a hash, a geographic location name, and so on.



Warning: If you select **EclecticIQ Observables CSV**, you need to choose at least one observable type from the **Observable types** drop-down list, and at least one enrichment observable type from the **Enrichment observable types** drop-down list.

If you select **EclecticIQ Observables CSV**, by default the outgoing feed includes only *first level*, *original* observables:

- **First level:** the extracted data is inside a CybOX object.
- **Original:** the value is extracted as is, that is, the observable holds the actual value found in the CybOX object.

You can include also *second level*, *derived* observables by selecting one or both checkboxes under **Content configuration**:

- **Include derived observables:** the extracted data is the result of an analysis of the original value found inside a STIX field.

- **Include secondary observables:** the source of the extracted data is a value inside a STIX field, not a value inside a CybOX object.

Create an automation user and group

It is a good idea to have one or more dedicated users and user groups, as necessary, to handle automation tasks that interact with external products or components of your system.

Automation groups bring together automation users, and they act as global controllers of the permissions the automation users require to operate.

Automation users handle automation and integration tasks such as data transmission through feeds and enrichers, or automatic entity creation as a follow-up action on a specific event.

Create an automation group



Warning: The automation group should include all the data sources — incoming feeds, enrichers, and groups — the automation users in the group need to access.

To add a new automation user group, do the following:

- On the left-hand navigation sidebar click **⚙ > User management**.
- Under **User management > Groups**, click the **+** icon. The user group editor is displayed.



Input fields marked with an asterisk are required.

- Under **Create group**, define the following configuration settings:
 - **Name:** a descriptive name for the automation user group.
Example: *DomainTools integration automation group*
 - **Description:** a short description of the automation user group and its purpose.
Example: *Automation group for DomainTools automation users*
 - **Allowed sources:** click **+ Add** or **+ More** to add new rows as needed, where you can enter additional criteria.
 - **Sources:** from the drop-down menu select one or more data sources the automation user group and its members can access to fetch data from. The data sources can be existing incoming feeds, enrichers, as well as other user groups.
 - **TLP:** from the drop-down menu select a **Traffic Light Protocol** (<https://www.us-cert.gov/tlp>) color to filter data accordingly.
 - Click **+ Add** or **+ More** to add new rows as needed, where you can enter additional criteria.
 - **Source reliability:** from the drop-down menu select a value to filter data source reliability, so as to allow the user group to access only data from reliable sources, based on the value you set here.
 - Click **Save** to store your changes, or **Cancel** to discard them.

Save options

Besides committing current data by clicking **Save**, you can also click the downward-pointing arrow on the **Save** button to display a context menu with additional save options:

- **Save and new**: saves the current data for the active item, and it allows you to start creating a new item of the same type right away. For example, a dataset, a feed, a rule, a workspace, or a task.
- **Save and duplicate**: saves the current data for the active item, and it creates a pre-populated copy of the same item, which you can use as a template to speed up manual creation work.

Create an automation role

To add a new automation role, do the following:

- On the left-hand navigation sidebar click **⚙ > User management**.
- Under **User management > Roles**, click the **+** icon. The role editor is displayed.

✓ Input fields marked with an asterisk are required.

- Under **Create role**, define the following configuration settings:
 - **Name**: a descriptive name for the automation role.
Example: *Rule modifier*
 - **Description**: a short description of the automation role and its purpose.
Example: *This role allows a third-party product to modify platform rules.*
 - **Permissions**: from the drop-down menu select the actions the role is allowed to perform.

Alternatively:

- Start typing a permission name in the autocomplete text input field.
- Select one or more filtered permissions from the list.
- To revoke one or more permissions for the role, click the **✕** icon corresponding to the permission you want to remove, or the **✕** icon next to the drop-down arrow in the input field to remove all permissions at once.
- Click **Save** to store your changes, or **Cancel** to discard them.

About permissions

- Permissions are associated with roles. Roles act as containers for sets of permissions defining the scope of actions of the corresponding roles.
- Permissions are predefined in the platform, and they are not editable or configurable. You can either grant them to roles, or revoke them.
- Permission names strive to be self-explanatory:
Format: *<type of action> <object of the action>*
Example: *modify entities*

- Permissions allow two types of action:
 - **modify**: a modification permission that allows write operations.
 - **read**: a read permission that grants access to data without allowing any modifications.

To get an overview of the available permissions available on the platform, do the following:

- On the left-hand navigation sidebar click **⚙ > User management**.
- Under **User management > Permissions**, the permission overview is displayed as a table, where each permission is assigned a row.
You can sort the items on the view by column header. To do so, click the column header you want to base the data sorting on. An upward-pointing ▲ or a downward-pointing ▼ arrow in the header indicates ascending and descending sort order, respectively.

Create an automation user

To add an automation user, do the following:

- On the left-hand navigation sidebar click **⚙ > User management**.
- Under **User management > User**, click the **+** icon.
The user editor is displayed.

✓ Input fields marked with an asterisk are required.

In the user editor define the following configuration settings:

- **First name**: enter a name that provides a short description of the automation role and its purpose.
- **Last name**: enter a name that provides a short description of the automation role and its purpose.
- **User name**: enter the designated user name to identify the user, when signed in to the platform.
Choose a name that helps understand what the automation user does.
Example: *DomainTools integration connector*
- **Email**: an email address associated with the automation user. You can use this address to send and receive automated notifications.
- **Active**: select this checkbox to enable the user immediately after saving the newly created user profile.
Active users can sign in to the platform and carry out actions, based on their user profile and their permissions.
- **Administrator**: select this checkbox to elevate the user's role to administrator.
When the checkbox is selected, the user has full administrator rights and permissions.
- **Contact info**: n/a
- **PGP public key**: the user's **PGP public key** (<https://ssd.eff.org/en/module/introduction-public-key-cryptography-and-pgp>).
- **Locale**: from the drop-down menu select the appropriate **locale** ([https://en.wikipedia.org/wiki/locale_\(computer_software\)](https://en.wikipedia.org/wiki/locale_(computer_software))) settings for the user interface.
- **Use system timezone**: select this checkbox to override any locale-specific time zone setting with the system-defined time zone.
- **Groups**: from the drop-down menu select one or more groups to assign the new user to.
Alternatively, search for a group by starting typing a group name in the autocomplete text input field.
- To remove the user from one or more groups, remove the relevant entries by clicking the **✕** corresponding to the group you want to remove the user from.

- **Roles:** it works like **Groups**, the only difference being that instead of adding the user to one or more groups, this option assigns one or more roles to the user.
- Click **Save** to store your changes, or **Cancel** to discard them.

Get the automation group meta.source ID

Platform entities include a `meta.source` property key/value pair to identify the platform group as a data source.

If you want to programmatically create entities in the platform, you need to pass a group `meta.source` ID value when you make the corresponding calls to the platform API.

Likewise, if you want to identify the platform source group an entity comes from when the platform transmits data to an external product or system, you can retrieve the `meta.source` property key/value pair.

To retrieve the correct `meta.source` ID value related to an automation group, do the following:

- Get the automation group ID.
- Pass the automation group ID to get the `meta.source` ID.

Step 1 of 2: get the group ID

To retrieve the automation group ID value you need, so that you can retrieve the `meta.source` ID you pass in the calls to the platform API, do the following:

- On the left-hand navigation sidebar click **⚙ > User management**.
- Under **User management**, click **Groups**.
- On the platform group overview page, click the row corresponding to the automation group associated with the data source(s) you want to use as input *and* to the automation user making the API calls.
- The action returns a URL with the following format:
`https://<platform_host>/user-management/groups?detail=<integer>`
Example: `https://platform.host/user-management/groups?detail=30`

In the example, the `detail` value is `30`. This is the group ID.

You need to pass this value in a call to a specific platform API endpoint to retrieve the `meta.source` ID.

Step 2 of 2: get the group source ID

To retrieve the `meta.source` ID to make calls to the platform API to programmatically create entities, do the following:

- Make an authentication call to the platform API to validate your user credentials and to receive a Bearer token.
- Make a call to the `/api/groups/<group_ID>` endpoint:
 - Include the Bearer token in a `Bearer` header in the call.
 - Include the group ID you previously retrieved as a trailing element in the URL.
Example: `https://platform.host/api/groups/30`
- In the JSON response, look for the group object with the `"id" : <integer>` key/value pair matching the group ID you previously retrieved.
Example: `"id" : 30,`
- In the same group object, look for the `"source" : "<UUID_string>"` key/value pair.
This is the group `meta.source` ID you need to pass in API calls to programmatically create entities.

Get the automation group meta.source ID example

Get the group ID

- On the platform group overview page, click the row corresponding to the automation group associated with the data source(s) you want to use as input.

```
https://platform.example.com/user-management/groups?detail=30
```

cURL API request — fetches the group meta.source

```
$ curl -X GET
-v
--insecure
-i
-H "Content-Type: application/json"
-H "Accept: application/json"
-H "Authorization: Bearer <token>"
https://platform.host/api/groups/30

# copy-paste version:
$ curl -X GET -v --insecure -i -H "Content-Type: application/json" -H "Accept: application/json"
-H "Authorization: Bearer <token>" https://platform.host/api/groups/30
```

API response — returns the group meta.source

```
{
  // Number of returned user groups
  "count": 18,

  "data": [

    ...

    {
      "allowed_sources": [

        // Lists all allowed data sources configured in the group editor
        ...

      ],

      // Group id, same value as the 'detail=' URL param for the group
      "id": 30,

      // Group 'meta.source' ID you need to pass in API calls
      "source": "42c051f8-9f5b-4696-a629-b86c2ead955f",

      // Group 'meta.source_name', the group name defined in the group editor
      "name": "DomainTools automation group",

      "type": "groups",
      "users": [

        // Lists all users that are part of the group
        ...

      ]
    },

    ...

  ]
}
```

Authentication

The authentication mechanism is based on **JSON web tokens** (<http://jwt.io/>).

By default, the token expires 30 minutes after successfully signing in. The corresponding session is terminated, and you need to sign back in to the platform.

When human interaction is detected — for example, keystrokes or mouse activity — the token is automatically refreshed every 2 minutes. This prevents the system from signing out users who may be working or saving data at that time.

Therefore, the default maximum amount of idle time without any human interaction before being automatically signed out equals to *session token validity - 2 minutes*.

To authenticate and access the platform, do the following:

- Make a `POST` call.
- In the call, pass your authentication credentials as a JSON object to the `/auth` endpoint. The credential data is used to generate a token that is returned with the response.

You need to include the generated bearer token in the `Authorization` HTTP header with each subsequent API call. The `Authorization` HTTP header has the following format: `Authorization: Bearer <token>`

Auth request

API endpoint	<code>/auth</code>
Auth method	<code>POST</code>
HTTP headers	<code>"Content-Type: application/json", "Accept: application/json"</code>
API request	<code>POST + "Content-Type: application/json" + "Accept: application/json" + { "username": "<valid_user_name>", "password": "<valid_password>" } + <platform_host>/api/auth</code>
API response	<code>{ "expires_at": "<expiry timestamp>", "token": "<token>" }</code>

The following example uses cURL to authenticate:

```
$ curl -X POST
  --insecure
  -H "Content-Type: application/json"
  -d '{ "username" : "<valid_user_name>", "password" : "<valid_password>" }'
  https://platform.host/api/auth

# copy-paste version:
$ curl -X POST --insecure -H "Content-Type: application/json" -d '{ "username" : "  
<valid_user_name>", "password" : "<valid_password>" }' https://platform.host/api/auth
```

Auth response

When the user name and password credential are valid, the `POST` call returns a JSON web token:

```
{
  "expires_at": "2016-03-30T12:11:40.078219+00:00",
  "token"      :
  "abHpYXQiOjE0NTkzMzI3MDAsIm4TcCI6MTQ1OTMzOTkwMCwiYWxnIjoiSFMyNTYifQ.oyY1c2VyX2lkIjoiLQ. LQQ3NdUHp4s-  
QCXsq3feI0Dy6tf5XQX9DOML1RNIzQ"
}
```

You need to include the bearer token value in each subsequent API call. You pass the token by including an `Authorization` HTTP header in the API request.

The `Authorization` HTTP header has the following format: `Authorization: Bearer <token>`

In the following example, you make a `GET` request to the `/api/` endpoint to retrieve a list of the available API endpoints and the corresponding methods:

```
$ curl -X GET
  -v
  --insecure
  -i
  -H "Content-Type: application/json"
  -H "Accept: application/json"
  -H "Authorization: Bearer <token>"
  https://platform.host/api/

# copy-paste version:
$ curl -X GET -v --insecure -i -H "Content-Type: application/json" -H "Accept: application/json"
-H "Authorization: Bearer <token>" https://platform.host/api/
```



Warning:

About cURL calls

- If you make HTTPs cURL calls to the API *and* you have a self-signed or an invalid certificate, include the `-k` or the `--insecure` parameter in the cURL call to skip the SSL connection CA certificate check.
- Always append a `/` trailing slash at the end of an API URL endpoint. The only exception is `/auth`, which does not take a trailing forward slash.
- In the cURL call, the `-d` data payload with the entity information always needs to be flat JSON, not hierarchical JSON.
If you want to pass a hierarchical JSON object, include the `--data-binary` parameter, followed by the path to the JSON file, for example `@/path/to/entity_file.json`.

Get the feed ID

You can access and download content from an outgoing feed by specifying its ID. A feed ID is included in the outgoing feed URL as a URL parameter.

Get the feed ID through the GUI

To get the feed ID through the platform GUI, do the following:

- On the top navigation bar, select **Data configuration > Outgoing feeds**.
- On the top-left corner of the page click the **+** icon to open the outgoing feed editor.
- On the **Outgoing feeds** overview, browse to the feed whose ID you need to retrieve, and then click the corresponding row.
- The outgoing feed URL is loaded on the web browser address bar. For example:
`https://<platform.domain>/#/configuration/outgoing-feeds?detail=78&tab=detail`
- The `detail` URL parameter holds the feed ID.
In the example URL, `detail=78` indicates that the selected outgoing feed ID is `78`.
When you make an API call to retrieve the feed content, you need to include the ID value in the API endpoint.

Get the feed ID through the API

Make an API call to download a list of all available public outgoing feeds.

This call returns a JSON object with an array listing all available public outgoing feeds with HTTP transport type.

API endpoint	/open-outgoing-feed-download/
API method	GET
HTTP headers	"Content-Type: application/json", "Accept: application/json", "Authorization: Bearer <token>"
API request	GET + "Content-Type: application/json" + "Accept: application/json" + "Authorization: Bearer <token>" + <platform_host>/open-outgoing-feed-download/
API response	{ "data" : [<open_outgoing_feed_array>] }

API request outgoing feeds

cURL call

```
$ curl -X GET
-v
--insecure
-i
-H "Content-Type: application/json"
-H "Accept: application/json"
-H "Authorization: Bearer <token>"
https://platform.host/api/open-outgoing-feed-download/

# copy-paste version:
$ curl -X GET -v --insecure -i -H "Content-Type: application/json" -H "Accept: application/json"
-H "Authorization: Bearer <token>"
```

API response outgoing feeds

```
{
  "data": [
    {
      "id": 1,
      "link": "/api/open-outgoing-feed-download/1",
      "name": "Default outgoing feed"
    },
    {
      "id": 16,
      "link": "/api/open-outgoing-feed-download/18",
      "name": "Public feed with electrolytes"
    },
    {
      "id": 25,
      "link": "/api/open-outgoing-feed-download/25",
      "name": "XYZ"
    }
  ]
}
```

Get a specific outgoing feed

Make an API call to download the details of a specific outgoing feed.

This call returns a JSON object containing the details of a specific public outgoing feed with HTTP transport type.

To select the public outgoing feed whose details you want to retrieve, include the feed ID in the API request endpoint.

API endpoint	/open-outgoing-feed-download/<feed-id>/
API method	GET
HTTP headers	"Content-Type: application/json", "Accept: application/json", "Authorization: Bearer <token>"
API request	GET + "Content-Type: application/json" + "Accept: application/json" + "Authorization: Bearer <token>" + <platform_host>/open-outgoing-feed-download/<feed-id>/
API response	{ "data" : { <specific_feed_details> } }

API request specific outgoing feed

cURL call

```
$ curl -X GET
  -v
  --insecure
  -i
  -H "Content-Type: application/json"
  -H "Accept: application/json"
  -H "Authorization: Bearer <token>"
  https://platform.host/api/open-outgoing-feed-download/18

# copy-paste version:
$ curl -X GET -v --insecure -i -H "Content-Type: application/json" -H "Accept: application/json"
-H "Authorization: Bearer <token>" https://platform.host/api/open-outgoing-feed-download/18
```

API response specific outgoing feed

The response details include an array listing the successful feed executions.

The paths in the `content_blocks` array have the following format:

```
/api/open-outgoing-feed-download/<feed-id>/runs/<run-id>/content-blocks/<content-block-id>
```

- A *run* is a feed execution to publish the feed content.
- A *content block* is a data blob whose format depends on the content type defined for the feed. For example, JSON, CSV or STIX.

```
{
  "data": {
    "content_blocks": [
      "/api/open-outgoing-feed-download/18/runs/0ad2edd4-8a7b-4894-b8b3-ae90a22ebaa/content-blocks/32",
      "/api/open-outgoing-feed-download/18/runs/5fdeff71-93af-43a5-b94e-c4ab857a749c/content-blocks/33",
      "/api/open-outgoing-feed-download/18/runs/40e31ada-06e6-4647-a287-4c9b54841619/content-blocks/34",
      "/api/open-outgoing-feed-download/18/runs/0f56ec9c-cc1e-4aae-afd0-f693f412ad55/content-blocks/35",
      "/api/open-outgoing-feed-download/18/runs/d842dd68-8ecf-4ecf-b073-a591d361cf26/content-blocks/36",
      "/api/open-outgoing-feed-download/18/runs/eed28e1e-4352-42a5-8b1f-cfc918b0e0ab/content-blocks/37",
      "/api/open-outgoing-feed-download/18/runs/f830aa7b-4ddc-4725-b13c-7cbe445f306d/content-blocks/40",
      "/api/open-outgoing-feed-download/18/runs/a11bb585-720a-4c56-b650-90cb9d6a69e5/content-blocks/41",
      "/api/open-outgoing-feed-download/18/runs/6e677f4b-c91d-49dd-9c39-70266987b863/content-blocks/42"
    ],
    "id": 18,
    "name": "Public feed with electrolytes"
  }
}
```

Install and configure EclecticIQ Platform App for Splunk

EclecticIQ Platform App for Splunk is a native application that installs directly on your Splunk instance.

This section describes how to download and install EclecticIQ Platform App for Splunk, as well as how to configure Splunk to work with the app.

Download the app

- Download the *eclecticiq-platform-app-for-splunk-<version_number>.tgz* file from **Splunkbase** (<https://splunkbase.splunk.com/app/3408/>).
- Save the archive locally.

Install the app

- In the Splunk management console go to **Apps > Manage Apps**, and then click **Install app from file**.
- Browse to the location where the *eclecticiq-platform-app-for-splunk-<version_number>.tgz* file is stored, and then click **Upload**.
- After successfully completing the upload and the installation, restart Splunk.

Configure the app

After restarting Splunk, you can proceed to configuring EclecticIQ Platform App for Splunk.

- In the Splunk management console go to **Apps**.

- From the app list select **EclecticIQ Platform App for Splunk**.
- On the displayed dialog window click **Continue to app setup page**.

EclecticIQ Platform App for Splunk configuration

Feeds setup

ID of feeds for collection from EclecticIQ Platform (comma separated, for example: 5, 6)

Note: You need to pre-configure feeds in EclecticIQ Platform. Please read install guide.

Input setup

Indexes (comma separated)

Sourcetypes (comma separated)

Select the type of Sighting to send to EclecticIQ Platform

- ipv4
- ipv6
- domains
- hash-md5
- hash-sha1
- hash-sha256
- hash-sha512
- emails

EclecticIQ Platform url

url of EclecticIQ Platform (for example: https://10.10.14.108/)

Verify SSL Connection

Verify the SSL Connection if SSL is used

EclecticIQ Platform source group name

EclecticIQ Platform source group name

EclecticIQ Platform authentication

Username


Password

Confirm password

On the EclecticIQ Platform App for Splunk configuration screen, define the following options:

- **Feeds setup:** enter the feed ID of the EclecticIQ Platform outgoing feeds whose content you want to send to Splunk. If you enter multiple feed IDs, use a comma (,) as a separator. Example: 4,18,74,88

- **Input setup:** define the indexes and the source types you are using as data sources for this integration:
 - **Indexes:** enter the name of the **Splunk indexes** (<http://docs.splunk.com/splexicon:index>) you want to include as sources.
Events included in the specified input indexes are searched for matches against the criteria defined in this configuration.
Matching events are used to create sightings.
If you enter multiple indexes, use a comma (,) as a separator.
To view a list with the available Splunk indexes, in Splunk go to **Settings > Indexes**.
Default value: * (asterisk, that is, all available Splunk indexes are included as sources)
 - **Sourcetypes:** enter the name of the **Splunk source types** (<https://docs.splunk.com/splexicon:sourcetype>) you want to include.
Events whose data structure corresponds to the specified input source types are searched for matches against the criteria defined in this configuration.
Matching events are used to create sightings.
If you enter multiple source type names, use a comma (,) as a separator.
Splunk includes a **built-in source type set** (<http://docs.splunk.com/documentation/splunk/latest/data/listofpretrainedsourcetypes>).
Default value: * (asterisk, that is, all available source types are included as sources)
Example: *access_combined,linux_messages_syslog*



- **Select the type of Sighting to send to EclecticIQ Platform**: select all applicable checkboxes corresponding to the data types you want to use to generate the sightings that are subsequently sent for ingestion to EclecticIQ Platform. Supported types:
 - *ipv4*
 - *ipv6*
 - *domains*
 - *hash-md5*
 - *hash-1*
 - *hash-256*
 - *hash-512*
 - *email*
- **EclecticIQ platform URL**: enter the URL corresponding to the address of the EclecticIQ Platform host. Example: *https://10.10.10.10/* or *https://platform.instance.org/*
- **Verify SSL Connection**: select this checkbox to enable SSL verification for the connection, if it uses SSL.
- **EclecticIQ source group name**: enter the name of the group you want to use as a source. A valid group name corresponds to the name of any available group configured in the platform. Example: *Sightingbusters*
- **EclecticIQ platform authentication**: enter valid credentials to authenticate and to sign in to the platform; that is, a valid user name and a password, which you need to confirm.
- Click **Save** to save and store your configuration.


Configure data model acceleration

By default, **data model acceleration**

(<https://docs.splunk.com/documentation/splunk/latest/knowledge/acceleratedatamodels>) is configured to speed up data models within 7 days.

To modify the data model acceleration settings, do the following:

- In Splunk, go to **Settings > Data models**.



- Browse to the **Eclectiq** row, and then select the **Edit > Edit Acceleration** menu option.

Data Models

Data models enable users to easily create reports in the Pivot tool. [Learn More](#)

1 Data Models App: Eclectiq Platform App for Splunk (eclectiq-platform-app-for-splunk) Created in the App Owner: Any

i	Title ^	Type	⚡	Actions
>	Eclectiq	data model	⚡	Edit ▾ Pivot

- Edit Datasets
- Edit Permissions
- Edit Acceleration
- Clone

- In the displayed dialog window, make sure the **Accelerate** checkbox is selected.
- From the **Summary Range** drop-down menu, select the time interval you want data to base acceleration on.

Edit Acceleration [X]

Data Model: EIQ

Accelerate:

Acceleration may increase storage and processing costs.

Summary Range? 1 Day ▾

Cancel Save

- Click **Save** to save and store your edits.

Default job schedule

- By default, a script is configured to run and collect outgoing feeds once every 2 hours at *hour:00 mins*; that is, at 00:00, 02:00, 04:00, and so on.
- By default, a script is configured to push sightings once a day at 01:00 AM.

Customize the job schedule

You can change the job schedules in the following configuration file:

`$SPLUNK_HOME/etc/apps/eclecticiq-platform-app-for-splunk/default/inputs.conf`

This is the default version of the file that ships with the app:

```
[default]

[script://$SPLUNK_HOME/etc/apps/eclecticiq-platform-app-for-splunk/bin/eiq_send_sightings.py]
disabled = false
interval = 00 01 * * *

[script://$SPLUNK_HOME/etc/apps/eclecticiq-platform-app-for-splunk/bin/eiq_collect_feeds.py]
disabled = false
interval = * */2 * * *

[script://$SPLUNK_HOME/etc/apps/eclecticiq-platform-app-for-splunk/bin/eiq_setup_handler.py]
passAuth = splunk-system-user

[script://$SPLUNK_HOME/etc/apps/eclecticiq-platform-app-for-splunk/bin/eiq_collect_feeds.py]
passAuth = splunk-system-user

[script://$SPLUNK_HOME/etc/apps/eclecticiq-platform-app-for-splunk/bin/eiq_send_sightings.py]
passAuth = splunk-system-user
```

- `eiq_collect_feeds.py` is the script that collects outgoing feed data from EclecticIQ Platform. To change the script execution schedule, edit the corresponding `interval` cron expression.
- `eiq_send_sightings.py` is the script that sends sightings to EclecticIQ Platform. To change the script execution schedule, edit the corresponding `interval` cron expression.

For further details on Splunk cron expressions, see the official **Splunk documentation on cron expressions**

(http://docs.splunk.com/documentation/splunk/latest/alert/definescheduledalerts#using_cron_expressions
and their **answers to common questions on cron expressions**

(<https://answers.splunk.com/answers/120603/cron-expression-in-splunk.html>).

After correctly configuring EclecticIQ Platform App for Splunk to integrate and work with Splunk, the corresponding dashboard view should become populated with relevant results.